

DS-7616NI-I2(C)
16-ch 1U 4K NVR


- Up to 16 channel IP cameras can be connected
- Up to 1-ch@32 MP/2-ch@12 MP/16-ch@1080p decoding capacity
- 1 HDMI and 1 VGA interfaces: both interfaces support independent video output
- 2 HDDs for continuous video recording
- Supports various special function cameras, including thermal camera/fisheye/people counting/heatmap/ANPR (automatic number plate recognition)
- Advanced streaming technology enables smooth live view and data self-correction in poor network conditions
- Supports dual-stream recording to save time and bandwidth
- Up to 8-ch IP speakers can be connected

▪ Specification

Video and Audio	
IP Video Input	16-ch Up to 12 MP resolution *: 32 MP and 24 MP is only available for channel 1 when ultra HD resolution mode is enabled.
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	256 Mbps
HDMI Output	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA Output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Video Output Mode	HDMI/VGA independent output
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264/MPEG4
Recording Resolution	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: 32 MP and 24 MP is only available for channel 1 when ultra HD resolution mode is enabled.
Synchronous Playback	16-ch
Decoding Capability	1-ch@32 MP (30 fps)/2-ch@12 MP (20 fps)/4-ch@8 MP (25 fps)/8-ch@4 MP (30 fps)/16-ch@1080p (30 fps)
Dual-Stream Recording	Support
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726
Network	
Remote Connection	128
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each HDD
Alarm In/Out	4/1
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
General	
Power Supply	12 VDC, 3.33 A
Consumption	≤15 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	384 × 317 × 52 mm (15.1" × 12.5" × 2.0")
Weight	≤ 1 kg (2.2 lb)
Certification	
CE	EN 55032:2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4

Obtained Certification

▪ Physical Interface




No.	Description	No.	Description
1	LAN interface	6	VGA output (DB9 connector)
2	AUDIO OUT	7	USB interface
3	AUDIO IN	8	Power supply
4	HDMI interface	9	GND
5	ALARM IN/OUT	10	Power switch

▪ Available Model

DS-7616NI-I2(C)

▪ Dimension



Unit:mm [inch]

SCALE	1:1
-------	-----

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®