

**DS-1600KI(B)  
Network Keyboard**

- High-performance, full-featured network keyboard
- Built-in Android system provides powerful control functions
- User friendly touch screen makes operation easy
- Flexible configuration via network
- Supports various cameras, NVRs and DVRs

## ▪ Specification

Interface	
USB Interface	2 × USB 2.0
Network Interface	10M/100M/1000M adaptive ethernet port; WiFi: Supported
General	
Working Temperature	-10 to +55° C (14 to 131° F)
Working Humidity	10% to 90%
Net Weight	1.7 kg (3.75 lb)
Dimensions (W × H × D)	404 mm × 163 mm × 180 mm (15.91" × 6.42" × 7.09")
Power Consumption	≤15 W
Power Supply	12 VDC/PoE
Display	10.1" TFT LCD touchscreen, Resolution: 1280 × 800
Joystick	4-axis joystick
Video	
Video Output Interface Type	1 ×HDMI, 1 ×DVI
Audio	
Audio Input Interfaces	1-ch, 3.5 mm connector (2.0 Vp-p, >1 KΩ)
Audio Output Interfaces	1-ch, 3.5 mm connector (2.0 Vp-p, 600 Ω)
Video Decoding	
Video Decoding Format	H.264, H.264+, H.265, H.265+, MPEG4
Video Decoding Capability	1 channel of 4K@30fps, or 4 channels of 1,080P@30fps
Certification	
Obtained Certification	CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/RCM/BIS

## ▪ Available Model

DS-1600KI(B)

DS-1600KI(STD)/ZAO Hikvision

DS-1600KI(B)/US Branch

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

