
DS-1LN6-UU
U/UTP Cat6 PVC 23AWG CPR Eca& UL CM Cable

Key Feature

- Stable electrical performance, compliant with ANSI/TIA-568.2-E, ISO/IEC 11801.
- Solid-Bare Copper conductor with less resistance, and better electrical properties and transmission performance.
- Sheath with strong mechanical properties, and high tensile and compressive strength, reducing damage during the project.
- With a flame-retardant sheath, for enhanced safety.
- Excellent performance in the Fluke permanent link test (90m) and channel test (100m).
- Support PoE application.
- Compliant with RoHS 2.0.





Specification

Model	DS-1LN6-UU	
Category	Cat.6	
Reference standard	ISO/IEC 11801, ANSI/TIA-568.2-E, RoHS 2.0	
Fire resistance	CPR Eca, UL CM	
Conductor	Material	Solid-Bare Copper (99.99%)
	Diameter	0.565± 0.005 mm 23AWG
Insulation	Material	HDPE
	Diameter	1.02 ± 0.05 mm
Sheath	Thickness	0.55 ± 0.05 mm
	Diameter	6.20 ± 0.50 mm
	Material	PVC
	Color	Orange
Rip-cord	Yes	
Separator	Yes	
Sheath physical properties	Before aging	Tensile strength ≥ 13.5 Mpa Elongation ≥ 150%
	Aging period	100°C × 24h × 7d
	After aging	Tensile strength ≥ 12.5 Mpa Elongation ≥ 125%
	Cold bend	(-20 ± 2)°C × 4h, 8 × cable O.D, no visible cracks
Electrical Characteristics (20°C)	1.0-250.0 MHz impedance	100 ± 15 Ω
	1.0-250.0 MHz delay skew	≤ 45 ns/100 m
	DC resistance	≤ 9.38 Ω/100 m
	DC conductor resistance unbalance	≤ 4.0%
	Package dimension	400 mm × 400 mm × 240 mm
	Weight	13.3± 1 kg
	Cable length	305 ± 1.5 m
	Operating temperature	-20°C to 70°C
	Operating voltage	≤57 V

Technical Performance (100 m)

Frequency (MHz)	ATT (20 ℃) ≤ (dB)	RL ≥(dB)	NEXT ≥(dB)	PS NEXT ≥(dB)	EL FEXT ≥(dB)	PS EL FEXT ≥(dB)	Phase delay ≤(ns)
1	2.03	20.0	74.3	72.3	67.8	64.8	570
4	3.78	23.0	65.3	63.3	55.8	52.8	552
8	5.32	24.5	60.8	58.8	49.7	46.7	547
10	5.95	25.0	59.3	57.3	47.8	44.8	545
16	7.55	25.0	56.2	54.2	43.7	40.7	543
20	8.47	25.0	54.8	52.8	41.8	38.8	542
25	9.51	24.3	53.3	51.3	39.8	36.8	541
31.25	10.67	23.6	51.9	49.9	37.9	34.9	540
62.5	15.38	21.5	47.7	45.4	31.9	28.9	539
100	19.80	20.1	44.3	42.3	27.8	24.8	538
200	28.98	18.0	39.8	37.8	21.8	18.8	537
250	32.85	17.3	38.3	36.3	19.8	16.8	536

Available Model

DS-1LN6-UU

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®