

THC-T120-PC 2 MP Indoor Fixed Turret Camera



- 1080p turret camera
- Smart IR, up to 20 m IR distance
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Model		THC-T120-PC
Interface	Video Output	1 HD analog output
	Switch Button	TVI/AHD/CVI/CVBS
Menu	Day/Night Mode	IR cut filter
	DWDR (Digital Wide Dynamic Range)	Support
	Language	English
	Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
	Backlight Compensation	Support
Camera	Image Sensor	2 MP CMOS image sensor
	Signal System	PAL/NTSC
	Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
	Resolution	1920 (H) × 1080 (V)
	Shutter Time	1/25 (1/30) s to 1/50,000 s
	Min. illumination	0.02 Lux@(F2.0, AGC ON), 0 Lux with IR
	Lens	2.8 mm, 3.6 mm
	Horizontal Field of View	2.8 mm, horizontal FOV: 92°, vertical FOV: 49°, diagonal FOV: 110° 3.6 mm, horizontal FOV: 75°, vertical FOV: 40°, diagonal FOV: 90°
	Lens Mount	M12
	Day & Night	IR cut filter
	Synchronization	Internal synchronization
	Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
General	Power Supply	12 VDC ± 15%
	Power Consumption	Max. 2.1 W
	Material	Plastic
	IR Range	Up to 20 m
	Dimensions	Ø 85.4 mm × 76.12 mm (Ø 3.38" × 2.67")
	Weight	130 g (0.29 lb.)
Operating Conditions		-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)

▪ Available Model

THC-T120-PC(2.8mm)

THC-T120-PC(3.6mm)

THC-T120-PC(3.6mm)(PT.VIVAN)

THC-T120-PC(RSA TRONITEK)

THC-T120-PC(2.8mm)(electropar)
 THC-T120-PC(2.8mm)(HIK BRA)
 THC-T120-PC(2.8mm)(CA4 TERANET)

▪ **Accessory**

▪ **Optional**

HIA-J101 Junction Box	HIA-B301 Vertical pole mount	HIA-B401-110T Wall Mount	HIA-B201 Corner mount
			

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HiLook