

THC-B120-MC 2 MP Fixed Mini Bullet Camera



- 1080p bullet camera
- Smart IR, up to 20 m IR distanceWater and dust resistant (IP66)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Model		THC-B120-MC
Camera	Image Sensor	2 MP CMOS image sensor
	Max. Resolution	1920 (H) × 1080 (V)
	Min. Illumination	0.02 Lux@(F2.0, AGC ON), 0 Lux with IR
	Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
	Day & Night	IR Cut Filter
	Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Lens	Lens Type	Fixed focal lens, 2.8 mm and 3.6 mm optional
	Focal Length & FOV	2.8 mm, horizontal FOV: 92°, vertical FOV: 49°, diagonal FOV: 110° 3.6 mm, horizontal FOV: 75°, vertical FOV: 40°, diagonal FOV: 90°
	Lens Mount	M12
Illuminator	Supplement Light Type	IR
	Supplement Light Range	Up to 20 m
Image	Image Parameters Switch	STD/HIGH-SAT
	Image Settings	Brightness, Mirror, Smart IR, Sharpness, AGC
	Frame Rate	PAL: 1080p @ 25 fps NTSC: 1080p @ 30 fps
	Day/Night Mode	Auto/Color/BW (Black and White)
	Wide Dynamic Range (WDR)	Digital WDR
	Image Enhancement	DWDR, BLC
	Noise Reduction	2D DNR
Interface	Video Output	Switchable TVI/AHD/CVI/CVBS
General	Power	12 VDC ±15%, Max. 2.9 W
	Material	Metal
	Dimension	165 mm × 62 mm × 58 mm (6.50" × 2.44" × 2.28")
	Weight	400 g (0.88 lb.)
	Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Approval	Protection	IP66

▪ Available Model

THC-B120-MC(2.8mm)

THC-B120-MC(3.6mm)

▪ **Accessory**

▪ **Optional**

HIA-J101
Junction Box



See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HiLook