

DS-K1T105

- IP-based Fingerprint Access Control Terminal
- 2.8-inch LCD display screen
- 100,000 cards, 300,000 events storage
- Communication via TCP/IP and Wi-Fi
- EHome for public network communication
- RS-485 and Wiegand interface
- Multiple time attendance status
- European power supply adaptor included (please mark for other standards when you order)

▪ Specification

General	
Working Temperature	-30°C to 65°C (-22°F to 149°F)
Working Humidity	10% to 90% (No Condensing)
Operation System	Linux
Working Current	Max. 500 mA
Power Supply	12 VDC
LED Indicator	Power/ Communication
Processor	32 Bit High-performance Processor
LCD Screen	320 × 240 (pixel) LCD-TFT Display Screen
Communication Mode	TCP/IP and Wi-Fi
Camera	2 MP
Storage	256M Storage
Card Capability	100,000 Cards and 300,000 Swiping Card Records
Input Interface	Doorbell × 1, Tamper Alarm × 1, Exit Button × 1, Door Magnetic Sensor × 1, Alarm Input × 2
Output Interface	Lock Relay × 1, Alarm Output × 1
USB Interface	USB 2.0
Key Board	17 Keys
Prompt	Beeper and Audio
Weight	280g
Dimension	137mm × 142mm × 35mm (5.4" × 5.6" × 1.4")

▪ Accessory

▪ Optional



See Far, Go Further



www.hikvision.com
support@hikvision.com

