

DS-3WR12GC(海外标配)/印度标 AC1200 Gigabit Port Wireless Router




DS-3WR12GC is a dual band Wi-Fi router designed by Hikvision. You can easily deploy, monitor and expand your home Wi-Fi network anytime and anywhere. DS-3WR12GC comes equipped with dual band coverage, which can offer a smooth online game and 4K video experience. Powered with beamforming technology, DS-3WR12GC ensures excellent high-speed Wi-Fi coverage in every corner at home.

- Four 5-dBi amplified antennas
- Beamforming optimizes signal
- Beamforming optimizes signal
- Dual band – Smart signal switching
- Dual band – Smart signal switching
- Broadband account synchronization

▪ Specification

General	
Product Dimension (W × H × D)	248.40 mm × 154.80 mm × 213.34 mm (9.78"× 6.09"× 8.40")
Package Dimension (W × H × D)	306 mm × 290 mm × 59 mm (12.05"× 11.42"× 2.32")
Net Weight	0.238 kg (0.525 lb)
Packing List	Wireless Router × 1, Ethernet cable × 1, Quick installation guide × 1
Packing Method	Single pack
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	10% to 90% RH non-condensing
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Storage Humidity	5% to 90% RH non-condensing
Installation Mode	Desktop installation
Max. Power Consumption	≤ 9 W
Gross Weight	0.738 kg (1.627 lb)
Wireless Parameter	
Data Rate	≤ 1167 Mbps 2.4 GHz: 300 Mbps 5 GHz: 867 Mbps
Wireless Standard	IEEE 802.11/a/n/ac wave 2 @5GHz, IEEE 802.11b/g/n @2.4GHz
Transmitting Power	18 dBm
Wireless Performance	4 × 4 MU-MIMO supported Beamforming supported
Receiving Sensitivity	58 ± 2 dB@AC80 -MCS9 84 ± 2 dB@AC80 -MCS0
Antenna	4 high gain antennas
Hardware Parameter	
Network Interface	4 × RJ45, 10/100/1000 Mbps auto-negotiation
LED Indicator	LED indicator
Reset	Reset button
Power Supply Method	9 VDC, 1 A power adapter power supply
Power Specifications	9 VDC, 1 A
Software Function	
Application function	Wireless Router Mode, Wireless Repeater Mode, Client + AP, WISP, and AP Mode supported DHCP Server supported Guest Network Configuration supported Signal Adjustment supported WiFi Schedule supported
Security Mode	WPA-PSK, WPA2-PSK, WPA and WPA2 supported
Security Mechanism	Hide SSID
Management Method	Web
Upgrade	Web Update and Upgrade
System Log	System log
WAN Mode	DHCP,Static IP,PPPoE


▪ Typical Application



▪ Available Model

DS-3WR12GC/印度标

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

