

DS-D44A0FO-GLF/C
P10 Outdoor Fixel LED Display Unit



- Support front and rear maintenance
- Using aluminum chassis, good heat dissipation and can work under 60 °C
- Apply unique technology, maximally saving 50% energy
- Various cabinet sizes, applying to diverse scenes
- The cabinets support customized 45° corner cut to realize 90° right-angle splicing

▪ Specification

Display	
White Balance Brightness	10000
Color Temperature	3000K-10000K
Viewing Angle	160° (H) /80° (V)
Brightness Uniformity	≥ 95%
Color Uniformity	≥ 95%
Contrast Ratio	8000:1
Cabinet	
Pixel Configuration	1R1G1B
Pixel Pitch Category	P10
Pixel Pitch	10mm
Modules Component	Aluminum bottom shell 120*240mm
Dimensions (W × H × D)	120*960*127
Resolution	12*96
Area	0.1152
Weight	5KG/PCS
Pixel Density	1152
Lamp Board Housing	Yes
Cabinet Material	Iron box
Maintenance Method	Back Maitence
Cabinet Flatness	0.8mm
Protection Level	IP67(F)/IP66(R)
Processing Performance	
Driving Method	Constant Current
Frame Frequency	50/60HZ
Refresh Rate	3840
Grey Level	14bit
Display Color	DCI-P3 > 85%
Power	
Power Supply	220
Power Consumption	≤ 650 W
Average Consumption	200
Max. Consumption	580
Working Environment	
Working Temperature	-40~+60°C
Working Humidity	10% to 95% RH (non-condensing)
Storage Temperature	-40~+80°C
Storage Humidity	10% to 95% RH (non-condensing)
General	
Package Dimensions (W × H × D)	1040mm*160mm*200mm
Gross Weight	10
Lifespan	100000 Hours

▪ **Available Model**

DS-D44A0FO-GLF/C

▪ **Accessory**

▪ **Included**



See Far, Go Further



www.hikvision.com
support@hikvision.com

