

AE-VC255T

- 2MP progressive scan CMOS
- Up to 1080P resolution
- Min. Illumination 0.1 lux @ (F1.2, AGC ON)
- Supports auto electronic shutter
- Supports auto gain control
- Adopts shock-proof design and aviation plug




▪ Specification

Camera	
Max. Resolution	1920*1080
Min. Illumination	0.1 Lux @ (F1.2, AGC ON)
Image Sensor	1/2.8" Progressive Scan CMOS
Shutter Speed	1/30 s to 1/22,500 s
Resolution	1920*1080
Lens Type	M12
Wide Dynamic Range	96 dB
Angle Adjustment	Tilt: 15 degree up/ 45 degree down
Lens	
Lens Type	6mm: Horizontal: 61° vertical: 33°, diagonal: 71°
Video	
Frame Rate	Compatible with 1080P@25fps/30fps, default 30fps
Image	
SNR	42 dB
General	
Product Weight	153.6 g (0.3 lb.)±5%
Power Supply	DC 9~16 V
Power Consumption	MAX. 1W
Camera Dimension	89.5±0.3mm*63.4±0.3mm*39.8±0.5mm
Storage Conditions	Storage Temp: -40~85°C Humidity: 45%-95%
Startup and Operating Conditions	Working Temp: -40~75°C
Cable Length	2.5 m (Support upper and lower outlet)

▪ Available Model

AE-VC255T(6mm)(上出线)(C)

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq