

DS-2CE16U0T-LF**4K Smart Hybrid Light Fixed Mini Bullet Camera**

- High quality imaging with 4K, 3840 × 2160 resolution
- 2.8 mm and 3.6 mm fixed focal lens
- Up to 30 m IR distance for bright night imaging
- Up to 20 m white light distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)
- Smart-Hybrid light, optimize your security with flexible lighting options

▪ Specification

Camera	
Image Sensor	4K CMOS
Max. Resolution	3840 (H) × 2160 (V)
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/12.5 s to 1/50,000 s NTSC: 1/15 s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm and 3.6 mm fixed focal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 108°, vertical FOV: 59°, diagonal FOV: 127° 3.6 mm, horizontal FOV: 88°, vertical FOV: 44°, diagonal FOV: 105°
Lens Mount	M12
Illuminator	
Supplement Light Range	IR : Up to 30 m White Light : Up to 20 m
Supplement Light Type	Smart,IR,White Light
Image	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 8 MP @12.5 fps, 8 MP @15 fps, 4 MP @25 fps, 4 MP @30fps, 2 MP @25 fps, 2 MP @30 fps AHD: 8MP@15fps CVI: 8MP@12.5fps, 8MP@15fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Power	12 VDC ± 25%, 0.45 A, max. 5.4 W,*You are recommended to use one power adapter to supply the power for one camera.
Material	Metal
Dimension	138.8 mm × Ø70 mm (5.46" × Ø2.76")
Weight	Approx. 265 g (0.59 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67




▪ Available Model

DS-2CE16U0T-LF(2.8mm)

DS-2CE16U0T-LF(3.6mm)

DS-2CE16U0T-LF(2.8mm)(ALG SARL)/SKD

▪ Dimension



▪ Accessory

▪ Optional

DS-1280ZJ-XS



See Far, Go Further



www.hikvision.com
support@hikvision.com

