

DS-PDMCK-EG2-WB(B) **Wireless Magnet Shock Detector**



- Magnetic contact combined with shock and tilt detection
- 2 wired inputs extension
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

▪ Specification

Detection Performance	
Detection Method	Opening Contact,Shock Sensor
Detection Gap	43mm Max
Sensitivity	Shock Detection: 8 levels Tilt Detection: Up to 25°
Feature	
Digital Processing	Support
Tamper Protection	Front,Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Interface	
Alarm Input	Normally Closed,Normally Open,Impulse Count
Power Switch	Power Up Enrolling
LED Indicator	Green(MC),Orange(tilt),Red(shock),Blue(alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433MHz
Transmission Security	Support
Transmission Range(Free Space)	1Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 3 years (standby time)
Power Supply	Battery Powered
Battery Type	CR123A x 1
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	24 × 104 × 24.4 mm 13 × 34.4 × 11.4 mm
Weight	60g
Application Scenario	Indoor

▪ Available Model



DS-PDMCK-EG2-WB(B)

DS-PDMCK-EG2-WB(B)/DZ/Epcom

DS-PDMCK-EG2-WB(B)/DZ

▪ Accessory

▪ Optional

DS-PDB-MCK-Brown n(B)	DS-PDB-MC-Adapter
	

See Far, Go Further



www.hikvision.com
support@hikvision.com

