

DS-K1T321MFWX-B **Value Series Face Access Terminal**



Face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster with higher accuracy. It also supports multiple authentication modes: face/card/fingerprint/PIN authentication, etc. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.

- 2.4-inch LCD screen, 2 MP lens
- Multiple authentication methods, including face, fingerprint, card (M1 card), and PIN, etc.
- Max. 500 faces, 3000 cards, 3000 fingerprints and 150,000 events
- Face recognition duration < 0.2 s/User
- Supports ISAPI and ISUP 5.0 protocols
- Configuration via the PC web client and mobile web client
- Supports wired network and Wi-Fi (AP mode)
- Supports wiring with secure door control unit or card reader via RS-485
- Supports power supply by battery in the bracket
- Supports access control and local time and attendance function
- Supports Push SDK.
- Supports face duplicate check, preventing multiple people from using the same face.
- Supports attendance-only function.


▪ Specification

System	
Operating system	Linux
Display	
Screen size	2.4 inch
Type	LCD
Resolution	320 × 240
Video	
Lens	1
Resolution	2 MP (video stream: 720P)
Video standard	PAL (Default) and NTSC
Audio	
Audio output	Built-in buzzer
Network	
Wired network	Support 10/100/1000 Mbps self-adaptive
Interface	
Network interface	1 RJ-45, 10/100 M self-adaptive
Lock control	1
Exit button	1
Door contact input	1
TAMPER	1
RS-485	1 RS-485 (Half duplex, HIKVISION)
USB	1
Capacity	
Face capacity	500
Fingerprint capacity	3000
Card capacity	3000
Event capacity	150,000
Authentication	
Face recognition distance	0.3 m ~ 1.5 m
Face recognition accuracy rate	> 99%
Face recognition duration	< 0.2 s
Card type	M1 card
General	
Power supply	12 VDC Supports power supply by battery in the bracket
Power consumption	≤ 6 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 90% (No condensing)
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Brazilian Portuguese, Japanese, Korean, Chinese Traditional, French, Turkish, Kazakh and Uzbek.
Keypad	Support
Function	
Face anti-spoofing	Support

Face recognition

Support

▪ Dimension



Unit: mm [inch]

SCALE	1:1
-------	-----

See Far, Go Further



www.hikvision.com
support@hikvision.com

