DS-7608NI-M2/8P(M)
8-ch 1U 8 PoE 8K NVR





- H.265+/H.265/H.264+/H.264 video formats
- Up to 8-ch IP camera inputs
- Up to 40 x 1080p@ 30fps decoding capacity
- Up to 128 Mbps incoming bandwidth
- Up to 8-ch IP speakers can be connected

***Professional and Reliability*
**1、 H.265+ compression effectively reduces the storage space by up to 75%*
**2、Dual-stream recording saves bandwidth*
**3、Adopt stream over TLS encryption technology which provides more secure stream transmission service*
**4、Support double verification for playback and downloading*
**HD Video Output*
**1、Provide independent HDMI and VGA outputs*
**2、HDMI video output at up to 8K resolution*
**Storage and Playback*
**1、Up to 2 SATA interfaces for HDD connection*
**2、8-ch synchronous playback*
**Smart & POS Function*
**1、Support multiple VCA (Video Content Analytics) events*
**2、Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR, and *people counting*
**3、POS information overlay on live view and playback, and POS triggered recording and alarm*
**Network & Ethernet Access*
**1、8 independent PoE network interfaces*
**2、1 self-adaptive 10/100/1000 Mbps Ethernet interface*
**3、Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management*
**4、Smooth streaming technology*
**5、Support web access without plug-in*


▪ Specification

Video and Audio	
IP Video Input	8-ch Up to 32 MP resolution *: The NVR supports up to 8-ch 32/24/16 MP IP video inputs.
Incoming Bandwidth	128 Mbps
Outgoing Bandwidth	256 Mbps
HDMI Output	8K(7680x4320)/30HZ，4K(3840×2160)/60Hz,4K(3840×2160)/30Hz ,2K(2560×1440)/60Hz，1080P(1920×1080)/60Hz
VGA Output	1080P(1920×1080)/60Hz
Video Output Mode	HDMI/VGA independent output
CVBS Output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Decoding	
Dual-Stream Recording	Support
Decoding Format	H.265+/H.265/H.264+/H.264
Decoding Capability	2-ch@32 MP (30 fps); 3-ch@24 MP (30 fps); 5-ch@16MP (30 fps); 6-ch@12MP (30 fps);8-ch@8 MP (30 fps);
Synchronous Playback	8-ch
Recording Resolution	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2/PCM
Network	
Remote Connection	128
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS, ONVIF(Version 2.2), OTAP
Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Camera Access Protocol	ONVIF(Version 2.5), RTSP
PoE	
Interface	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤ 120 W
Standard	IEEE 802.3 af/at
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 20 TB capacity for each disk
Alarm In/Out	4/1
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
General	
Power Supply	100 to 240 VAC, 50 to 60 Hz
Consumption	≤ 50 W (without HDD and PoE off)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	385 × 315× 52 mm (15.2" × 12.4" × 2.0")


Weight	≤ 3.3 kg (without HDD, 7.3 lb.)
Certification	
CE	EN 55032:2015+A1:2020, ENIEC61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020
Cyber Security	
EN 303645	Support
Secure Boot	Support
Secure Component Verification SVC	Support
Password Protection	Support
IP & MAC Address Filtering	Support
HTTPS Encryption	Support
Live View & Playback Stream Encryption	Support
IEEE802.1X(EAP-TLS) Network Access Control	Support
Signed Firmware	Support
Ohters	Digest authentication User access log Centralized certificate management Brute force delay protection

▪ Physical Interface

No.	Description	No.	Description
1	Network interfaces with PoE function	6	VGA interface
2	LAN interface	7	USB 3.0 interface and CVBS video output
3	Audio in and audio out	8	Power switch
4	HDMI interface	9	GND
5	Alarm in and alarm out	10	100 to 240 VAC power supply



▪ Dimension



Unit:mm [inch]

SCALE	1:1

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®