

DS-PR1-WB(B) **Wireless Repeater Plus**



The wireless repeater, supporting 433 Mhz wireless communication, Tri-X and Cam-X wireless protocol, multiple enrollment methods, two-way wireless communication, and auto-pairing, is used for extending RF distance in alarm system.

- 433 MHz two-way wireless communication
- Two-way communication, stable and secure
- LED display, show the differernt feedbacks with easy understanding
- Up to 24 hrs battery backup after mains lost, no worry about communication
- Finding and connecting up to 8 PIRCAM or smoke detectors automatically, smart auto-pairing
- Easy installation with new designed structure

▪ Specification

Software features	
Auto pairing	Supported
Hardware features	
Serial port	2, for debug
Tamper-Proof	1, front and back
Power switch	1
Electrical characteristics	
Battery type	Built in Battery Li
Power supply	100 VAC to 240 VAC
Operation humidity	10% to 90%
Operation temperature	-10°C to +55°C (The battery can not be charged at temperature lower than 0°C, please make sure the adapter is connected)
Battery life span	Up to 24 hours at normal temperature(The battery working time can be significantly reduced at low temperatures)
Wireless transmission	
RF frequency	433 MHz
RF method	Two-way communication
RF modulation	2GFSK
RF distance	800 m (open area)
Wireless security	AES-128
General	
Installation method	Wall mounting
Dimension(WxHxD)	170.0 × 170.0 × 38.6 mm
Shell material	Plastic
Color	White
Weight	526.5 g

▪ Available Model

DS-PR1-WB(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq