


iDS-6732NXI-M1/AI(B) NVS DeepinMind




- Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080P decoding capacity
- H.265+/H.265/H.264+/H.264 video formats
- Up to 32-ch IP cameras can be connected
- Deep learning based video analytics for not wearing hard hat detection and event detection, including people running detection, people gathering detection, violent motion detection, using mobile phone detection, etc

▪ Specification

AI Open Platform Performance	
Live Video Analysis	2 engines in total, one engine can support up to 4ch, (4ch@4MP, 2ch@6MP, 1ch@8MP)
Auto-Switch Video Analysis	2 engines in total, one engine can support up to 16ch, (switch time between 10 to 3600 seconds)
Scheduled Capture Analysis	2 engines in total, one engine can support up to 16ch, (switch time between 3 to 3600 seconds)
Video and Audio	
IP Video Input	32-ch
Incoming Bandwidth	256Mbps
Outgoing Bandwidth	256 Mbps
Video Output Mode	HDMI1/VGA1 simultaneous output, HDMI2/VGA2 simultaneous output
Audio Output	1-ch, RCA (Linear, 1 K Ω)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)
HDMI Output	HDMI1 : 8K (7680 $\times$ 4320)/30 Hz, 4K (3840 $\times$ 2160)/60 Hz, 4K (3840 $\times$ 2160)/30 Hz, 2K (2560 $\times$ 1440)/60 Hz, 1080P (1920 $\times$ 1080)/60 Hz HDMI2 : 4K (3840 $\times$ 2160)/60Hz, 4K (3840 $\times$ 2160)/30Hz, 2K (2560 $\times$ 1440)/60Hz, 1920 $\times$ 1080/60Hz *: When HDMI 1 output resolution is 8K, the maximum HDMI 2 output resolution is 1080p.
VGA Output	VAG1/VGA2:1080P (1920 $\times$ 1080)/60 Hz
Decoding	
Decoding Format	H.265/H.265+/H.264/H.264+
Decoding Capability	Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080P
Synchronous Playback	16-ch
Recording Resolution	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: NVR supports up to 8-ch 32 MP/24 MP IP video inputs.
Network	
Remote Connection	128
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
API	ONVIF (profileS/G); SDK; ISAPI
Compatible Browser	IE11, Chrome V57, Firefox V52, Safari V12, Edge V89, or above version
Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 16 TB capacity for each HDD, 1 built-in 3.5-inch 2 TB SATA hard disk
Serial Interface	1 RS-232 interface, 2 RS-485 interface
USB Interface	Rear panel: 2 $\times$ USB 2.0; Rear panel: 1 $\times$ USB 3.0
Alarm In/Out	16/4


General	
GUI Language	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish Language, Norwegian, Finnish, Korean, Traditional Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Ukrainian, Kyrgyz, Brazilian Portuguese, Indonesian
Power Supply	12 VDC, 5A
Consumption	≤ 60 W
Working Temperature	-10 to 55° C (14 to 131° F)
Working Humidity	10 to 90%
Dimension (W × D × H)	320 × 243 × 65 mm (12.6 × 9.6 × 2.6 inch)
Weight	≤ 5kg
Intelligent Analytics	
AI by NVR	Pre-installed AI Algorithm Package Human (3 Algorithm models) 1. Facial recognition: 2. People counting: regional people counting, people counting statistics 3. PPE: safety helmets and reflective vests detection Vehicle (2 Algorithm models) 1. Vehicle attributes: vehicle brand, vehicle color, vehicle type 2. Non-motorized vehicle detection: motorcycle, bicycles Dangerous Event (2 Algorithm models) 1. Fire and smoke detection 2. Occupation of fire escape Behavior (3 Algorithm models) 1. Street level behavior : falling down detection, people gathering detection, fast moving detection, physical conflict detection 2. Indoor: playing phone, sleeping on duty, absence, number of people allowed, overstaying detection 3. Perimeter: intrusion detection, line crossing detection, region entrance detection, region exiting detection 4. Smoke detection, call detection AIOP (Up to 16 models) Model type: detection model, classification model, mixed model (detection model and classification model) 1 engines in total, One engine can support four algorithm models; each algorithm model supports one real-time video stream analysis or a maximum of 8 auto-switch video analyses (switch time between 10 to 3600 seconds)
Engine	3 * KT2 (2 for live video analysis, 1 for lager model algorithm secondary analysis)
AI Open Platform Performance	
Offline Picture Analysis	4 image per GPU per second or 1 image per GPU per second (Large model)

▪ Physical Interface



No.	Description	No.	Description
1	USB interfaces	7	USB 3.0 interface
2	eSATA interface	8	Alarm in, alarm out, and RS-485
3	LAN interfaces	9	Power switch
4	Audio in and audio out	10	Power supply
5	HDMI interfaces	11	GND
6	VGA interface and RS-232 interface		

▪ Dimension



Unit:mm [inch]

SCALE 1:1



See Far, Go Further



www.hikvision.com
support@hikvision.com

