

**DS-VD22D-D/HW63E**

- Innovate at scale with challenging and emerging workloads, purpose-built for growing scale-out solutions
- Outmaneuver threats with intelligence, automation, and recovery tools that include iDRAC9 Telemetry, BIOS live scanning, and Rapid OS recovery
- Supports multiple management models, best to manage your device. 1:1 or 1:Many; Full remote control and management functions.
- Feature-optimized server with ideal selection of CPU, I/O, and storage performance for scale-out environments to meet data needs, suitable for various scale scenarios

## ▪ Specification

Model		DS-VD22D-D/HW63E
Hardware Specifications	CPU	4515Yx2 /5418Yx2
	Memory	512GB
	Hard Disks	Standard config: 960GB SSD×2(RAID_1)+1.6T NVME U.2 SSD×4+8T 7.2K SATA HDD×6(RAID_10)
	Storage Controller	Standard Config: H755 8G RAID card
	Supported Operating Systems	Without any OS pre-installed
	PCIe Slots	Two Slots Capability: 2× Semi-high Gen 5 PCIe slots; 4× Semi-high Gen 4 PCIe slots
Management	Remote Manage	iDrac9 Enterprise
	OpenManage™ Software	Support OpenManage Enterprise and Plugins (PowerManager, SupportAssist, and Update Manager)
	Integrations and Connections	Integrations: Microsoft® System Center, VMware® vCenter™, BMC Truesight (available from BMC), Red Hat Ansible; Connections: Nagios Core & Nagios XI, Micro Focus Operations Manager i (OMi), IBM Tivoli Netcool / OMNIbus
	Security	Support Cryptographically signed firmware; Secure Boot; Secure Erase; Silicon Root of Trust; System Lockdown (requires iDRAC9 Enterprise or Datacenter);
Ports	USB 3.0	0 (Front) +1 (Rear)
	USB 2.0	1 (Front) +1 (Rear)
	Ethernet Port	1GbE×2+10GbE×2
	VGA	2
	iDRAC Direct (Micro-AB USB) Port	1
	iDRAC Ethernet Port	1
	Manager Port	1
General	Net Weight	36.1 kg (79.58 lb)
	Gross Weight	53.4 kg (117.73 lb)
	Dimension (W × H × D)	482.0 mm × 86.8 mm × 772.13 mm (18.97" × 3.41" × 30.39")
	Package Dimensions (W × H × D)	667.0 mm × 327.0 mm × 1010.0 mm (26.26" × 12.87" × 39.76")
	Operating Temperature	10 °C to 35 °C (50 °F to 95 °F)
	Storage Temperature	-40 °C to 65 °C (-104 °F to 149 °F)
	Operating Humidity	8% to 80% (no condensation)
	Storage	5% to 95% (no condensation)

	Humidity	
	Power Supply	1400 W, 50/60 Hz, 100-240 VAC (Auto adjustment), 12-8 A
	Form Factor	2U Rack

▪ **Available Model**

DS-VD22D-D/HW63E

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

