

**DS-D4019CC-1F****DS-D4019CC-1F 1000\*250/mm**


- **Multiple dimensions:** Cabinets with various dimensions can be flexibly used to meet a variety of plane and three-dimensional stitching needs.
- **Light and ultra-thin cabinets:** Ultra-thin and die casting aluminum cabinets are light and beautiful, which can help to deliver quickly.
- **Delicate frame:** 45 degree frame structure with intensive design enhances the possibility of 90 degree right-angle of creative shapes installation. It can be used with more curved and creative stitching forms. There is no need to customize.
- **Magnetic module:** Standard lamp boards with precise locating structure and strong magnetic adsorption without bottom shell can benefit efficient installation and convenient maintenance.
- **Rotate to install:** Support cabinet and module 90 degree rotating installation and horizontal and vertical stitching of cabinets. No chromatic aberration in viewing angle.
- **Excellent display effect:** Support high definition display and color reproduction, high contrast ratio and high refresh rate. Adopt Hikvision's dynamic engine algorithm for automatic screen control. The image is soft and comfortable to view.
- **Intelligent control system:** More intelligent with Hikvision's control system. Signal backup, intelligent operation and maintenance facilitate convenient operation and control. Support cloud management and maintenance.
- **High quality:** Obtained TUV-CE/ROHS/CB compliance certification. The cabinet is safe, reliable, energy-saving and environmentally friendly.

## ▪ Specification

Model		DS-D4019CC-1F
Display	White Balance Brightness	800 cd/m <sup>2</sup> (Peak 1000 cd/m <sup>2</sup> )
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P1.9
	Pixel Pitch	1.9531 mm
	Modules Component	1 × 4
	Dimensions (W × H × D)	1000 mm × 250 mm × 50 mm (39.370" × 9.843" × 1.969")
	Resolution	512 × 128
	Area	0.25 m <sup>2</sup> (387.501 in <sup>2</sup> )
	Weight	5.65 Kg (12.456 lb)
	Pixel Density	262144 dots/m <sup>2</sup>
	Lamp Board Housing	With housing
	Cabinet Material	Aluminium die casting
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm (0.00039")
	Protection Level	Front protection level IP60
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
Power	Power Supply	110 ~ 220 VAC ± 15%
	Max. Consumption	≤ 582 W/m <sup>2</sup>

	Average Consumption	< 194 W/m <sup>2</sup>
Working Environment	Working Temperature	-10 to 40 °C (14 °F to 104 °F)
	Working Humidity	10%~80%RH
	Storage Humidity	10%~80%RH
	Storage Temperature	-20 to 60 °C (-4 °F to 140 °F)
	Gross Weight	9.3 kg (34.488" x 5.354" x 12.992") (Carton, 1 cabinet in 1 box) 94 kg (36.023" x 40.984" x 27.755") (Carton, 10 cabinets in 1 box)
General	Package Dimension (W x H x D)	1180 mm x 136 mm x 330 mm (46.456" x 5.354" x 12.992") (Carton, 1 cabinet in 1 box) 1237 mm x 1041 mm x 652 mm (48.700" x 40.984" x 25.669") (Carton, 10 cabinets in 1 box)
	Lifespan	Lamp 100,000 hours
Bracket	Modular Bracket	DS-DL111025W 1*1; DS-DL211025W 2*1

## ▪ Typical Application




## ▪ Available Model

DS-D4019CC-1F 1000\*250MM/BOX(Stock)

DS-D4019CC-1F 1000\*250MM/BOX(Stock)/GOB

## ▪ Dimension



Unit: mm [inch]

SCALE 1:1

## ▪ Accessory

### ▪ Optional

DS-1NP6UEC0 CAT6 , U/UTP , 24AWG , CU	DS-D40CX-1F/PC CX Power Cable Pack	MCP200WS-4.5A-B CX Spare PSU	DS-D40CX-1F/H4 4 Ports Spare HUB Board	DS-D40CX-1F/R CX Spare Receiving Card
				

DS-D4019CX-1F/M  
CX Series P1.9 Spare

LED Module



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

**HIKVISION®**