

DS-D4039CF-1F**DS-D4039CF-1F 1000*500/mm**

无法显示链接的图像。该文件可能已被移动、重命名或删除。请验证该链接是否指向正确的文件和位置。

- Multiple dimensions: Cabinets with various dimensions can be flexibly used to meet a variety of plane and three-dimensional stitching needs.
- Light and ultra-thin cabinets: Ultra-thin and die casting aluminum cabinets are light and beautiful, which can help to deliver quickly.
- Delicate frame: 45 degree frame structure with intensive design enhances the possibility of 90 degree right-angle of creative shapes installation. It can be used with more curved and creative stitching forms. There is no need to customize.
- Magnetic module: Standard lamp boards with precise locating structure and strong magnetic adsorption without bottom shell can benefit efficient installation and convenient maintenance.
- Rotate to install: Support cabinet and module 90 degree rotating installation and horizontal and vertical stitching of cabinets. No chromatic aberration in viewing angle.
- Excellent display effect: Support high definition display and color reproduction, high contrast ratio and high refresh rate. Adopt Hikvision's dynamic engine algorithm for automatic screen control. The image is soft and comfortable to view.
- Intelligent control system: More intelligent with Hikvision's control system. Signal backup, intelligent operation and maintenance facilitate convenient operation and control. Support cloud management and maintenance.
- High quality: Obtained TUV-CE/ROHS/CB compliance certification. The cabinet is safe, reliable, energy-saving and environmentally friendly.

▪ Specification

Model		DS-D4039CF-1F
Display	White Balance	800 cd/m ² (Peak 1000 cd/m ²)
	Brightness	
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P3.9
	Pixel Pitch	3.90625 mm
	Modules Component	2 × 4
	Dimensions (W × H × D)	1000 mm × 500 mm × 50 mm(39.370" × 19.685" × 1.969")
	Resolution	256 × 128
	Area	0.5 m ²
	Weight	10.54 KG
	Pixel Density	65536 dots/m ²
	Lamp Board Housing	With housing
	Cabinet Material	Aluminium die casting
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP60
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
Power	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 494 W/m ²

	Average Consumption	< 165 W/m ²
Working Environment	Working Temperature	-10~40 °C
	Working Humidity	10%~80%RH
	Storage Humidity	10%~80%RH
	Storage Temperature	-20~60 °C
General	Gross Weight	20.4 kg (34.488" × 5.354" × 12.992") (Carton, 1 cabinet in 1 box) 102 kg (36.023" × 40.984" × 27.755") (Carton, 5 cabinets in 1 box)
	Package Dimension (W × H × D)	1180 mm × 136 mm × 605 mm (46.456" × 5.354" × 23.818") (Carton, 1 cabinet in 1 box) 1237 mm × 1041 mm × 652 mm (48.700" × 40.984" × 25.669") (Carton, 5 cabinets in 1 box)
	Lifespan	Lamp 100,000 hours
Bracket	Modular Bracket	DS-DL111050W 1*1;DS-DL211050W 2*1

▪ Typical Application



无法显示链接的图像。该文件可能已被移动、重命名或删除。请验证该链接是否指向正确的文件和位置。

▪ Available Model

DS-D4039CF-1F 1000*500MM/BOX(Stock)

DS-D4039CF-1F 1000*500/BOX(Stock)/NOVA/B

DS-D4039CF-1F 1000*500MM/BOX(Stock)/NOVA





▪ Dimension


 无法显示链接的图像。该文件可能已被移动、重命名或删除。请验证该链接是否指向正确的文件和位置。



▪ Accessory

▪ Optional

DS-1NP6UEC0 CAT6 , U/UTP , 24AWG , CU	DS-D40CX-1F/H8 8 Ports Spare HUB Board	MCP200WS-4.5A-B CX Spare PSU	DS-D40CX-1F/PC CX Power Cable Pack	DS-D40CX-1F/R CX Spare Receiving Card
				
DS-D4039CX-1F/M CX Series P3.9 Spare LED Module				



See Far, Go Further



www.hikvision.com
support@hikvision.com

