

**DS-D5043F3-1V0S(O-STD)(EU)@  
43 inch FHD 60Hz VA Monitor(EU)**



- Full HD 1920×1080 @60 Hz
- Wideviewing angle: Horizontal 178°, Vertical 178°.
- Ultra-thin device body with ultra-thin border for 3 sides.
- Multiple interfaces: HDMI, VGA, USB.
- Build-in speaker, Audio 10W\*2.
- Low blue light design for eye care.
- 3D noise reduction.
- Support VESA wall mount.

## ▪ Specification

| Display                        |                                                                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Screen Size                    | 43 inch                                                                                                                                                                                                                 |
| Active Display Area            | 950.896 (H) mm × 529.254 (V) mm                                                                                                                                                                                         |
| Resolution                     | 1920×1080 @60 Hz                                                                                                                                                                                                        |
| Backlight                      | D-LED                                                                                                                                                                                                                   |
| Pixel Pitch                    | 0.49005 (H) × 0.49005 (V) mm                                                                                                                                                                                            |
| Brightness                     | 300 cd/m2                                                                                                                                                                                                               |
| Viewing Angle                  | 178° / 178°                                                                                                                                                                                                             |
| Color Depth                    | 8 bit                                                                                                                                                                                                                   |
| Contrast Ratio                 | 4000 : 1                                                                                                                                                                                                                |
| Response Time                  | 6.5 ms (typ)                                                                                                                                                                                                            |
| Refresh Rate                   | 60 Hz                                                                                                                                                                                                                   |
| Haze                           | 25%                                                                                                                                                                                                                     |
| Color Gamut                    | 72% NTSC                                                                                                                                                                                                                |
| Reliability                    | 7 * 24H                                                                                                                                                                                                                 |
| Interface                      |                                                                                                                                                                                                                         |
| Video & Audio Input            | VGA × 1, HDMI 1.4 × 1                                                                                                                                                                                                   |
| Video & Audio Output           | LINE OUT × 1, Speaker OUT × 2 ( 8Ω 10W )                                                                                                                                                                                |
| Data Transmission Interface    | USB2.0 × 1                                                                                                                                                                                                              |
| Control Interface              | 无                                                                                                                                                                                                                       |
| Power                          |                                                                                                                                                                                                                         |
| Power Supply                   | 100~240 VAC, 50/60Hz, 1.0 A Max                                                                                                                                                                                         |
| Power Consumption              | ≤80W                                                                                                                                                                                                                    |
| Standby Consumption            | ≤ 0.5 W                                                                                                                                                                                                                 |
| Working Environment            |                                                                                                                                                                                                                         |
| Working Temperature            | 0 °C to 50 °C (41 °F to 104 °F)                                                                                                                                                                                         |
| Working Humidity               | 20% to 90% RH (Non-Condensing)                                                                                                                                                                                          |
| Storage Temperature            | -20 °C to 60 °C (14 °F to 140 °F)                                                                                                                                                                                       |
| Storage Humidity               | 5% to 90% RH (Non-Condensing)                                                                                                                                                                                           |
| General                        |                                                                                                                                                                                                                         |
| Speaker                        | 8 Ω 10 W ×2                                                                                                                                                                                                             |
| Casing Material                | Plastic                                                                                                                                                                                                                 |
| VESA                           | 200 mm × 200 mm ( 4 - M6 × 8 mm )                                                                                                                                                                                       |
| Bezel Width                    | 1.1 mm (top/left/right) , 24 mm (bottom)                                                                                                                                                                                |
| Product Dimensions (W × H × D) | Without base : 954.3(W) mm × 561.65(H) mm × 76.06(D) mm<br>37.57(W) inch × 22.11 (H) inch × 2.99 (D) inch ,<br>With base : 954.3(W) mm × 616.21(H) mm × 242.11(D) mm<br>37.57 (W) inch × 24.26 (H) inch × 9.53 (D) inch |
| Package Dimensions (W × H × D) | 1073(W)mm×668(H)mm×161(D) mm<br>(42.24 (W) × 26.3 (H) × 6.34 (D)) inch                                                                                                                                                  |
| Net Weight                     | 6.85 ± 0.5 kg (15.10 ± 1.1 lb.)                                                                                                                                                                                         |
| Gross Weight                   | 9.98 ± 0.5 kg (22.00 ± 1.1 lb.)                                                                                                                                                                                         |

|              |                                                                                                                                                                                                              |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packing List | Monitor × 1, Base component × 1, Power cable × 1, HDMI cable (1.5 m) × 1, User manual × 1, Multilingual manual × 1, Remote control × 1, Screw × 6                                                            |
| Remarks      | <p>*The base is included by default.</p> <p>*The product appearance and parameters in this specification may vary from your actual device. Please consult our local sales staff for further information.</p> |

## ▪ Physical Interface


| <div> <div>HDMI</div> <div>VGA</div> <div>USB</div> <div></div> </div> |                                                      |           |                                         |
|------------------------------------------------------------------------|------------------------------------------------------|-----------|-----------------------------------------|
| Interface                                                              | Description                                          | Interface | Description                             |
| AC                                                                     | AC,<br>100-240V~,50/60Hz,1.0A<br>Max,input interface | HDMI      | HDMI 1.4 digital signal input interface |
| VGA                                                                    | VGA analog signal input interface                    | USB       | USB2.0,input interface                  |
| Audio Out                                                              | 3.5mm Audio output interface                         |           |                                         |

## ▪ Available Model

DS-D5043F3-1V0S(EU)

## ▪ Dimension

- **Optional**



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

