



# HIKMICRO

## HM-TD8168-150ZE4F/G0/T2

Thermal & Optical Bi-spectrum Network Stable PTZ Camera



HIKMICRO Anti-corrosion Thermal Optical Bi-spectrum Network Stable Positioning System is applied to perimeter protection and fire-prevention purposes in scenes such as port, dock, island, aquafarm. The coating technology can meet the use requirements in anti-corrosion environment.

### ▪ Features

- 640\*512 resolution 12  $\mu\text{m}$ , NETD < 25 mK (25 °C, F# = 1.0)
- Perimeter protection function, based on intelligent algorithm: line crossing, intrusion, region entrance and exit
- Temperature exception alarm for fire prevention
- Fire detection and smoke detection algorithm
- Added one fixed lens overlaid on optical PTZ channel for wide-angle monitoring
- High quality detector with 10 years guarantee
- NEMA-4X Standard, Anti-corrosion coating

## • Specification

| Thermal Module         |                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor           | VOx Uncooled Focal Plane Arrays                                                                                                 |
| Resolution             | 640 × 512                                                                                                                       |
| Pixel Interval         | 12 μm                                                                                                                           |
| Response Waveband      | 8 μm to 14 μm                                                                                                                   |
| NETD                   | Less than 25 mK (@25°C,F#=1.0)                                                                                                  |
| Focal Length           | 19-150 mm                                                                                                                       |
| Focus Mode             | Semi-auto & Manual                                                                                                              |
| IFOV                   | 0.6-0.08 mrad                                                                                                                   |
| Aperture               | F0.85-1.2                                                                                                                       |
| Field of View          | 22.3°(H)*17.7°(V)-2.92°(H)*2.34°(V)                                                                                             |
| Min. Focusing Distance | 3m                                                                                                                              |
| Digital Zoom           | x2, x4, x8                                                                                                                      |
| Optical Module         |                                                                                                                                 |
| Image Sensor           | 1/1.8" Progressive Scan CMOS                                                                                                    |
| Resolution             | 2688 × 1520, 4 MP                                                                                                               |
| Min. Illumination      | Fixed Lens: Color: 0.0005 Lux @ (F1.0, AGC ON)<br>PTZ Lens: Color: 0.002 Lux @(F3.05, AGC ON), B/W: 0.0002 Lux@ (F3.05, AGC ON) |
| Field of View          | Fixed Lens: 89.46°(H) 47.92°(V)<br>PTZ Lens: 29.89°(H) 17.3°(V)-0.5°(H)0.26°(V)                                                 |
| Focal Length           | Fixed Lens: 4mm<br>PTZ Lens: 10-900mm                                                                                           |
| Aperture (Range)       | Fixed Lens: F1.0<br>PTZ Lens: F3.05-8.1                                                                                         |
| Shutter Speed          | 1/25 s to 1/30,000 s                                                                                                            |
| WDR                    | 120 dB                                                                                                                          |
| Digital Zoom           | x2, x4, x8, x16                                                                                                                 |
| Optical Defog          | PTZ lens support                                                                                                                |
| Focus Mode             | PTZ lens: semi-auto/manual                                                                                                      |
| Image Effect           |                                                                                                                                 |
| Picture in Picture     | Display partial image of one channel on the full screen of the other channel                                                    |
| Target Coloration      | Yes. Supported in white hot and black hot mode.                                                                                 |
| Image Stabilization    | Thermal channel supports EIS.<br>Optical PTZ lens supports OIS.                                                                 |
| PTZ                    |                                                                                                                                 |
| Movement Range         | Pan: 360° Continuous Rotate; Tilt: From -45° to + 45° (auto flip)                                                               |

|                         |                                                                                                                                                                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pan Speed               | Configurable, From 0.03°/s to 40°/s                                                                                                                                                                                                                         |
| Tilt Speed              | Configurable, From 0.02°/s to 15°/s                                                                                                                                                                                                                         |
| Proportional Zoom       | Yes                                                                                                                                                                                                                                                         |
| Presets                 | 300 in total                                                                                                                                                                                                                                                |
| Patrol Scan             | 8; Up to 32 Presets Per Patrol                                                                                                                                                                                                                              |
| Pattern Scan            | 4; More Than 10 Minutes Per Pattern                                                                                                                                                                                                                         |
| Power Off Memory        | Yes                                                                                                                                                                                                                                                         |
| Park                    | Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan                                                                                                                                                                    |
| PT Status               | Turn On/Turn Off                                                                                                                                                                                                                                            |
| Scheduled Task          | Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Doom Reboot/Doom Adjust/Aux Output                                                                                                                                 |
| <b>Smart Function</b>   |                                                                                                                                                                                                                                                             |
| VCA                     | VCA Support 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 50 scenes and 8 VCA rules for each scene                                                                                                                |
| Temperature Measurement | Support 3 temperature measurement rule types, 273 presets as scene, 21 rules of each scene (21 points, 21 areas, and 1 line)                                                                                                                                |
| Temperature Range       | -20 °C to 150 °C (-4 °F to 302 °F)                                                                                                                                                                                                                          |
| Temperature Accuracy    | ± 8 °C (±14.4 °F)                                                                                                                                                                                                                                           |
| Fire Detection          | Dynamic fire point detection, up to 10 fire points detectable.                                                                                                                                                                                              |
| Smoke Detection         | Up to 14km detection ability with 5m*5m smoke                                                                                                                                                                                                               |
| <b>Video and Audio</b>  |                                                                                                                                                                                                                                                             |
| Main Stream             | Optical channel<br>50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 960, 1280 × 720)<br>60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 960, 1280 × 720)<br>Thermal channel<br>50 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 512, 384 × 288) |
| Sub-stream              | Optical channel<br>50 Hz: 25fps (704 × 576, 352 × 288)<br>60 Hz: 30 fps (704 × 576, 352 × 288)<br>Thermal channel<br>50 fps (704 × 576, 640 × 512, 384 × 288)                                                                                               |
| Video Compression       | Main stream: H.265/ H.264<br>Sub-stream: H.265/H.264/MJPEG                                                                                                                                                                                                  |
| Audio Compression       | G722.1/G.711ulaw/G.711alaw/MP2L2/G.726/AAC/PCM                                                                                                                                                                                                              |
| <b>Video and Image</b>  |                                                                                                                                                                                                                                                             |
| Color Palettes          | 15 palettes (White hot, Black hot, Fusion 1, Rainbow, Fusion 2, Ironbow 1, Ironbow 2, Sepia, Color 1, Color 2, Icefire, Rain, Red hot, Green hot, Dark blue)                                                                                                |

## Network

|                        |                                                                                                                                |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Protocols              | IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE |
| Network Storage        | MicroSD/SDHC/SDXC card (up to 512 G) local storage, and NAS (NFS, SMB/CIFS), auto network replenishment (ANR)                  |
| API                    | ISAPI, HIKVISION SDK, third-party management platform, ONVIF (Profile S, Profile G, Profile T, Profile M)                      |
| Simultaneous Live View | Up to 20 channels                                                                                                              |
| User/Host level        | Up to 32 users, 3 levels: Administrator, Operator, User                                                                        |
| Security               | User authentication (ID and PW), MAC address binding, HTTPS encryption, IEEE 802.1x access control, IP address filtering       |
| Client                 | iVMS-4200, Hik-Connect                                                                                                         |
| Web Browser            | Live view (plug-in allowed) : Internet Explorer 11 Live view (plug-in free) :Chrome 91+、 Firefox 88+、 Safari 13+               |

## Interface

|                         |                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------|
| Alarm Input             | 7-ch inputs (0-5 VDC)                                                                              |
| Alarm Output            | 2-ch relay outputs, alarm response actions configurable                                            |
| Alarm Action            | Preset/Patrol Scan/Pattern Scan/SD Card Record/Relay Output/Smart capture/FTP upload/Email linkage |
| Audio Input             | LINE_IN Input/MIC Input; Peak: From 2 to 2.4V[p-p]; Output Impedance: 1KΩ±10%                      |
| Audio Output            | Linear Level; Impedance: 600 Ω                                                                     |
| Communication Interface | 1, RJ45 10 M/100 M Self-adaptive Ethernet interface.<br>1, RS-485 interface                        |
| Analog Video Output     | 1.0 V [p-p]/75 Ω, BNC for thermal channel                                                          |

## General

|                           |                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------|
| Power Supply              | 48 VDC ± 20%, two-core terminal block                                                            |
| Power Consumption         | Basic: < 190W; Max: < 270W (Heater on)                                                           |
| Work Temperature/Humidity | From -40°C to 70°C (-40°F to 158°F); Humidity: 95% or Less                                       |
| Wiper                     | Yes                                                                                              |
| Protection Level          | IP67 Standard<br>TVS 6000 V lightning protection, surge protection, voltage transient protection |
| Dimension                 | 649.2 mm × 438 mm × 668.3 mm (25.6 " × 17.2 " × 26.3 ")                                          |
| Weight                    | Approx. 60kg (132.3 lb)                                                                          |

## Detection Range Table

|                        |       |
|------------------------|-------|
| VCA Range for Humans   | 1950m |
| VCA Range for Vehicles | 4500m |

| Approval    |                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMC         | CE-EMC (EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN50130-4: 2011+A1: 2014);<br>RCM (AS/NZS CISPR 32: 2015);<br>IC (ICES-003: Issue 7) |
| Safety      | CB: IEC 62368-1: 2014+A11;<br>CE-LVD: EN 62368-1: 2014/A11: 2017;                                                                                           |
| Environment | CE-RoHS: 2011/65/EU,<br>WEEE: 2012/19/EU,<br>Reach: Regulation(EC) No 1907/2006                                                                             |
| Protection  | IP67: IEC 60529-2013                                                                                                                                        |
| Other       | NEMA 4X (NEMA 250-2018)<br>C5-ISO 12944-6:1998 C5 Medium & ISO 7253:1996 & ISO 6270-2:2017                                                                  |

## ▪ Range Table

The table is only for reference and the performance may vary according to different environment.

| VCA Range<br>(Vehicles: 1.4 × 4.0 m) | VCA Range<br>(Humans: 1.8 × 0.5 m) | VCA Range<br>(Vessels: 10 × 5 m) | Temperature<br>Measurement<br>(Object: 0.2 × 0.2 m) | Fire Detection<br>(Object: 1 × 1 m) | Smoke<br>Detection<br>(Object: 5 × 5 m) |
|--------------------------------------|------------------------------------|----------------------------------|-----------------------------------------------------|-------------------------------------|-----------------------------------------|
| 4500m                                | 1950m                              | 6000m                            | 500 m                                               | 6250 m                              | 16000m                                  |

## ▪ DORI

*\*The table is only for reference and the performance may vary according to different environment.*


*\*The optimal human detection, recognition, and identification distances are calculated according to Johnson' s Criteria.*

Detection Range: In order to distinguish an object from the background, the object must be covered by 1.5 or more pixels.

Recognition Range: In order to classify the object (animal, human, vehicle, etc.), the object must be covered by 6 or more pixels.

Identification Range: In order to identify the object and describe it in details, the object must be covered by 12 or more pixels.


| Detection Range<br>(Vehicles: 1.4 × 4.0 m) | Detection Range<br>(Humans: 1.8 × 0.5 m) | Recognition<br>Range (Vehicles:<br>1.4 × 4.0 m) | Recognition<br>Range (Humans:<br>1.8 × 0.5 m) | Identification<br>Range (Vehicles:<br>1.4 × 4.0 m) | Identification<br>Range (Humans:<br>1.8 × 0.5 m) |
|--------------------------------------------|------------------------------------------|-------------------------------------------------|-----------------------------------------------|----------------------------------------------------|--------------------------------------------------|
| 19167m                                     | 6250m                                    | 4792m                                           | 1563m                                         | 2396m                                              | 781m                                             |




## ▪ Available Model

HM-TD8168-150ZE4F/G0/T2

## ▪ Dimension



Unit:mm[Inch]



Unit:mm[Inch]

**COMPLIANCE NOTICE:** The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.

