

**DS-2CD2H86G2H-IZS2UY/S(L)(RB)****8MP Powered by Darkfighter Motorized Varifocal Turret Network Camera**

Powered by

**DarkFighter**

- Motorized varifocal lens for easy installation and monitoring
- Innovative socket design, highly waterproof and user-friendly
- Focus on person and vehicle classification based on deep learning
- Anti-corrosion design for stable protection (NEMA 4X)
- Water and dust resistant (IP67) and vandal resistant (IK10)
- Active strobe light and audio alarm to warn trespassers off
- Crystal clear audio with Arrayed Dual-Mic
- Clear imaging against strong back light due to 120 dB WDR technology
- Efficient H.265+ compression technology

## ▪ Specification

| Camera                      |                                                                                                                                                                                      |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor                | 1/1.8" Progressive Scan CMOS                                                                                                                                                         |
| Max. Resolution             | 3840 × 2160                                                                                                                                                                          |
| Min. Illumination           | Color: 0.0008 Lux @ (F1.2, AGC ON), B/W: 0 Lux with IR                                                                                                                               |
| Shutter Time                | 1/3 s to 1/100,000 s                                                                                                                                                                 |
| Day & Night                 | IR cut filter                                                                                                                                                                        |
| Angle Adjustment            | Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°                                                                                                                                 |
| Lens                        |                                                                                                                                                                                      |
| Lens Type                   | Varifocal lens, motorized lens, 2.8 to 12 mm                                                                                                                                         |
| Focal Length & FOV          | 2.8 to 12 mm, horizontal FOV 112.3° to 41.2°, vertical FOV 58.1° to 23.1°, diagonal FOV 137.4° to 47.3°                                                                              |
| Lens Mount                  | Integrated                                                                                                                                                                           |
| Aperture                    | Max. F1.2                                                                                                                                                                            |
| Depth of Field              | 1 m to ∞                                                                                                                                                                             |
| DORI                        |                                                                                                                                                                                      |
| DORI                        | Wide: D: 89.2 m, O: 35.4 m, R: 17.8 m, I: 8.9 m<br>Tele: D: 220.0 m, O: 87.3 m, R: 44.0 m, I: 22.0 m                                                                                 |
| Illuminator                 |                                                                                                                                                                                      |
| Supplement Light Type       | IR                                                                                                                                                                                   |
| Supplement Light Range      | Up to 40 m                                                                                                                                                                           |
| Smart Supplement Light      | Yes                                                                                                                                                                                  |
| IR Wavelength               | 850 nm                                                                                                                                                                               |
| Video                       |                                                                                                                                                                                      |
| Main Stream                 | 50 Hz: 25 fps (3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)<br>60 Hz: 24 fps (3840 × 2160), 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)            |
| Sub-Stream                  | 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)                                                                                 |
| Third Stream                | 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>*Third stream is supported under certain settings. |
| Video Compression           | Main stream: H.265/H.264/H.264+/H.265+, ,<br>Sub-stream: H.265/H.264/MJPEG, ,<br>Third stream: H.265/H.264, ,<br>*Third stream is supported under certain settings.                  |
| Video Bit Rate              | 32 Kbps to 16 Mbps                                                                                                                                                                   |
| H.264 Type                  | Baseline Profile, Main Profile, High Profile                                                                                                                                         |
| H.265 Type                  | Main Profile                                                                                                                                                                         |
| Bit Rate Control            | CBR, VBR                                                                                                                                                                             |
| Scalable Video Coding (SVC) | H.264 and H.265 encoding                                                                                                                                                             |
| Region of Interest (ROI)    | 1 fixed region for main stream and sub-stream                                                                                                                                        |
| Audio                       |                                                                                                                                                                                      |
| Audio Compression           | G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC                                                                                                                                             |
| Audio Bit Rate              | 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)                                                    |

|                             |                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio Sampling Rate         | 8 kHz/16 kHz/32 kHz/48 kHz                                                                                                                                                                                                                                                                                                                                                            |
| Environment Noise Filtering | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Network</b>              |                                                                                                                                                                                                                                                                                                                                                                                       |
| Protocols                   | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets, SRTP, SFTP                                                                                                                                                                                               |
| Simultaneous Live View      | Up to 6 channels                                                                                                                                                                                                                                                                                                                                                                      |
| API                         | ONVIF (ProfileS, ProfileT, ProfileG), ISAPI, SDK, ISUP                                                                                                                                                                                                                                                                                                                                |
| User/Host                   | Up to 32 users<br>3 user levels: administrator, operator, and user                                                                                                                                                                                                                                                                                                                    |
| Security                    | Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.1/1.2/1.3, host authentication (MAC address) |
| Network Storage             | NAS (NFS, SMB/CIFS), Auto Network Replenishment (ANR)                                                                                                                                                                                                                                                                                                                                 |
| Client                      | iVMS-4200, Hik-Connect, Hik-Central                                                                                                                                                                                                                                                                                                                                                   |
| Web Browser                 | Plug-in required live view: IE 10, IE 11,<br>Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Edge 89+,<br>Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+                                                                                                                                                                                                                   |
| <b>Image</b>                |                                                                                                                                                                                                                                                                                                                                                                                       |
| Image Parameters Switch     | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| Image Settings              | Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser                                                                                                                                                                                                                                                           |
| Day/Night Switch            | Day, Night, Auto, Schedule                                                                                                                                                                                                                                                                                                                                                            |
| Wide Dynamic Range (WDR)    | 120 dB                                                                                                                                                                                                                                                                                                                                                                                |
| SNR                         | ≥ 52 dB                                                                                                                                                                                                                                                                                                                                                                               |
| Image Enhancement           | BLC, HLC, 3D DNR                                                                                                                                                                                                                                                                                                                                                                      |
| Privacy Mask                | 4 programmable polygon privacy masks                                                                                                                                                                                                                                                                                                                                                  |
| <b>Interface</b>            |                                                                                                                                                                                                                                                                                                                                                                                       |
| Ethernet Interface          | 1 RJ45 10 M/100 M self-adaptive Ethernet port                                                                                                                                                                                                                                                                                                                                         |
| On-Board Storage            | Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB                                                                                                                                                                                                                                                                                                     |
| Built-in Speaker            | Max. power consumption: 2 W, max. sound pressure level: 10 cm: 97 dB.                                                                                                                                                                                                                                                                                                                 |
| Audio                       | Built-in Microphone: Arrayed dual-microphone,<br>1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium,<br>1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium                                                       |
| Alarm                       | 1 input, 1 output (max. 24 VDC/24 VAC, 1 A)                                                                                                                                                                                                                                                                                                                                           |
| Reset Key                   | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Event</b>                |                                                                                                                                                                                                                                                                                                                                                                                       |
| Basic Event                 | Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception                                                                                                                                                                                                                                                           |
| Smart Event                 | Scene change detection                                                                                                                                                                                                                                                                                                                                                                |
| Linkage                     | Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, trigger capture, audible warning, strobe light flashing                                                                                                                                                                                                               |

| Deep Learning Function           |                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Perimeter Protection             | Line crossing, intrusion, region entrance, region exiting<br>Support alarm triggering by specified target types (human and vehicle)                                                                                                                                                                                                                   |
| Face Capture                     | Yes                                                                                                                                                                                                                                                                                                                                                   |
| General                          |                                                                                                                                                                                                                                                                                                                                                       |
| Power                            | 12 VDC $\pm$ 25%, 1.4 A, max. 16.8 W, 2-core terminal block, reverse polarity protection, PoE: IEEE 802.3at, Class 4, max. 20 W                                                                                                                                                                                                                       |
| Material                         | Base: Metal, cover: Metal                                                                                                                                                                                                                                                                                                                             |
| Dimension                        | $\varnothing$ 143.5 mm $\times$ 142.7 mm ( $\varnothing$ 5.7" $\times$ 5.6")                                                                                                                                                                                                                                                                          |
| Package Dimension                | 170 mm $\times$ 170 mm $\times$ 225 mm (6.7" $\times$ 6.7" $\times$ 8.9")                                                                                                                                                                                                                                                                             |
| Weight                           | Approx. 1265 g (2.8 lb.)                                                                                                                                                                                                                                                                                                                              |
| With Package Weight              | Approx. 1525 g (3.4 lb.)                                                                                                                                                                                                                                                                                                                              |
| Storage Conditions               | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                             |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                             |
| Language                         | 33 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function                 | Heartbeat, mirror, password reset via email, pixel counter, anti-banding                                                                                                                                                                                                                                                                              |
| Flashing Light                   | -SL: White Light<br>-SRB: Red and Blue Light                                                                                                                                                                                                                                                                                                          |
| Approval                         |                                                                                                                                                                                                                                                                                                                                                       |
| EMC                              | CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021                                                                                                                                                                                                                              |
| Safety                           | CB: IEC 62368-1:2014+A11                                                                                                                                                                                                                                                                                                                              |
| Environment                      | CE-RoHS: 2011/65/EU,<br>WEEE: 2012/19/EU,<br>Reach: Regulation (EC) No 1907/2006, NEMA 4X (NEMA 250-2018)                                                                                                                                                                                                                                             |
| Protection                       | IP67: IEC 60529-2013, IK10: IEC 62262:2002                                                                                                                                                                                                                                                                                                            |

## ▪ Available Model


DS-2CD2H86G2H-IZS2UY/SL(2.8-12mm)

DS-2CD2H86G2H-IZS2UY/SRB(2.8-12mm)

DS-2CD2H86G2H-IZS2UY/SL(2.8-12mm)(Black)

DS-2CD2H86G2H-IZS2UY/SRB(2.8-12mm)(Black)

## ▪ Dimension



Unit: mm(inch)

## ▪ Accessory

### ▪ Optional

| DS-1476ZJ-SUS | DS-1475ZJ-SUS | DS-1273ZJ-140B-Y | DS-1271ZJ-140-Y | DS-1273ZJ-140-Y |
|---------------|---------------|------------------|-----------------|-----------------|
|               |               |                  |                 |                 |

## ▪ Installation Methods

| Corner Mounting<br>DS-1476ZJ-SUS+DS-1253ZJ-L+DS-1273ZJ-140B-Y | Vertical Pole Mounting<br>DS-1475ZJ-SUS+DS-1253ZJ-L+DS-1273ZJ-140-Y | Wall Mounting<br>DS-1273ZJ-140B-Y+DS-1253ZJ-L | Wall Mounting<br>DS-1273ZJ-140-Y | Pendant Mounting<br>DS-1271ZJ-140-Y |
|---------------------------------------------------------------|---------------------------------------------------------------------|-----------------------------------------------|----------------------------------|-------------------------------------|
|                                                               |                                                                     |                                               |                                  |                                     |

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

