

## DS-7632NXI-K2/16P(E) 32-ch PoE 1U K Series AcuSense 4K NVR



- Adopt Hikvision Acusense technology to minimize manual effort and security costs
- Efficient playback with AcuSearch technology
- Accurate perimeter protection effectively reduces false alarms
- Automatic cameras connection and configuration
- Up to 32-ch IP camera inputs, plug & play with 16 Power-over-Ethernet (PoE) interfaces
- H.265+/H.265/H.264+/H.264 video formats
- Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity
- Up to 256 Mbps incoming bandwidth

## ▪ Specification


| Model                 |                                            | DS-7632NXI-K2/16P(E)(标配)                                                                                                                           | DS-7632NXI-K2/16P(E)(中性) |
|-----------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Intelligent Analytics | AI by NVR                                  | Facial recognition, perimeter protection, motion detection 2.0, AcuSearch                                                                          |                          |
|                       | AI by Camera                               | Facial recognition, perimeter protection, motion detection 2.0, ANPR                                                                               |                          |
| Facial Recognition    | Facial Detection and Analytics             | Face picture comparison, human face capture, face picture search                                                                                   |                          |
|                       | Facial Detection and Analytics Performance | Up to 4 MP: 2-ch;<br>8 MP to 5 MP: 1-ch                                                                                                            |                          |
|                       | Face Picture Library                       | Up to 16 face picture libraries, with up to 50,000 face pictures in total (each picture ≤ 1 MB, total capacity ≤ 1 GB)                             |                          |
|                       | Face Picture Comparison                    | 8-ch                                                                                                                                               |                          |
| AcuSearch             | By Camera                                  | All channels<br>*: The camera should enable AcuSearch function                                                                                     |                          |
| Motion Detection 2.0  | By NVR                                     | All channels, up to 4 MP (when enhanced SVC mode is enabled, up to 8 MP) video analysis for human and vehicle recognition to reduce false alarm    |                          |
|                       | By Camera                                  | All channels                                                                                                                                       |                          |
| Perimeter Protection  | By NVR                                     | Video analysis (HD network camera, H.264/H.265) for human and vehicle recognition to reduce false alarm.<br>Up to 4 MP : 2-ch; 5 MP to 8 MP : 1-ch |                          |
|                       | By Camera                                  | All channels                                                                                                                                       |                          |
| Video and Audio       | IP Video Input                             | 32-ch                                                                                                                                              |                          |
|                       | IP Speaker Input                           | 4-ch                                                                                                                                               |                          |
|                       | Incoming Bandwidth                         | 256 Mbps                                                                                                                                           |                          |
|                       | Outgoing Bandwidth                         | 160 Mbps                                                                                                                                           |                          |
|                       | HDMI Output                                | 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz         |                          |
|                       | VGA Output                                 | 1-ch, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz                                                                        |                          |
|                       | Video Output Mode                          | HDMI/VGA independent output                                                                                                                        |                          |

|                            |                      |                                                                                                                                                                                                                  |
|----------------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                            | Audio Output         | 1-ch, RCA (Linear, 1 K $\Omega$ )                                                                                                                                                                                |
|                            | Two-Way Audio        | 1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ , using the audio input)                                                                                                                                                       |
| <b>Decoding</b>            | Decoding Format      | H.265/H.265+/H.264/H.264+                                                                                                                                                                                        |
|                            | Recording Resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF /2CIF/CIF/QCIF                                                                                                                                     |
|                            | Synchronous playback | 16-ch                                                                                                                                                                                                            |
|                            | Decoding Capability  | AI on: 16-ch@1080p (30 fps)<br>AI off: 20-ch@1080p (30 fps)                                                                                                                                                      |
|                            | Stream Type          | Video, Video and Audio                                                                                                                                                                                           |
|                            | Audio Compression    | G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2                                                                                                                                                                        |
| <b>Network</b>             | Remote Connection    | 128                                                                                                                                                                                                              |
|                            | API                  | ONVIF (profile S/G); SDK; ISAPI                                                                                                                                                                                  |
|                            | Compatible Browser   | IE 11, Chrome 91, Firefox 88, Safari 12, Edge 91, or above version                                                                                                                                               |
|                            | Network Protocol     | TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS                                                                                                           |
|                            | Network Interface    | 1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface                                                                                                                                                       |
| <b>PoE</b>                 | Interface            | 16, RJ-45 10/100 Mbps self-adaptive Ethernet interface                                                                                                                                                           |
|                            | Power                | ≤ 200W                                                                                                                                                                                                           |
|                            | Standard             | IEEE 802.3af/at                                                                                                                                                                                                  |
| <b>Auxiliary Interface</b> | SATA                 | 2 SATA interfaces                                                                                                                                                                                                |
|                            | Capacity             | Up to 16 TB capacity for each HDD                                                                                                                                                                                |
|                            | Alarm In/Out         | 4/1                                                                                                                                                                                                              |
|                            | USB Interface        | Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0                                                                                                                                                                |
| <b>General</b>             | GUI Language         | English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish, Norwegian, Finnish, Korean, Traditional |

|               |                        |                                                                                                                                              |
|---------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
|               |                        | Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Hebrew, Ukrainian, Indonesian |
|               | Fan                    | Supports automatic speed control                                                                                                             |
|               | Power Supply           | 100 to 240 VAC, 50 to 60 Hz                                                                                                                  |
|               | Consumption            | ≤ 15 W (without HDD)                                                                                                                         |
|               | Working Temperature    | -10 °C to 55 °C (14 °F to 131 °F)                                                                                                            |
|               | Working Humidity       | 10% to 90%                                                                                                                                   |
|               | Dimension (W × D × H)  | 384 mm × 317 mm × 52 mm (15.12 × 12.48 × 2.03 inch)                                                                                          |
|               | Weight                 | ≤ 2.5 kg (without HDD, 5.5 lb.)                                                                                                              |
| Certification | CE                     | EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017                                                                       |
|               | Obtained Certification | CE,CB,REACH,WEEE,UKCA,RCM,IC                                                                                                                 |

## ▪ Function

## ▪ Physical Interface




| No. | Description                          | No. | Description              |
|-----|--------------------------------------|-----|--------------------------|
| 1   | Network interfaces with PoE function | 7   | VGA interface            |
| 2   | LAN network interface                | 8   | USB interface            |
| 3   | AUDIO OUT                            | 9   | GND                      |
| 4   | AUDIO IN                             | 10  | AC100V~240V power supply |
| 5   | HDMI interface                       | 11  | Power switch             |
| 6   | Alarm in/alarm out                   |     |                          |

## ▪ Available Model

DS-7632NXI-K2/16P(E)(STD)

DS-7632NXI-K2/16P(E)(NEU)

## ▪ Dimension



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

