

DS-7716NXI-K4(E)

- Automatic speed control fans are designed for running quietly and energy saving
- Adopt Hikvision AcuSense technology to minimize manual effort and security costs
- Efficient playback with AcuSearch technology
- Accurate perimeter protection effectively reduces false alarms
- Automatic cameras connection and configuration
- Up to 16-ch IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity
- Up to 160 Mbps incoming bandwidth

▪ Specification

Model		DS-7716NXI-K4(E)(标配)	DS-7716NXI-K4(E)(标配)/IO16+9	DS-7716NXI-K4(E)(中性)	DS-7716NXI-K4(E)(中性)/IO16+9
Intelligent Analytics	AI by NVR	Facial recognition, perimeter protection, motion detection 2.0, AcuSearch			
	AI by Camera	Facial recognition, perimeter protection, motion detection 2.0, ANPR			
Facial Recognition	Facial Detection and Analytics	Face picture comparison, human face capture, face picture search			
	Facial Detection and Analytics Performance	Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch			
	Face Picture Library	Up to 16 face picture libraries, with up to 50,000 face pictures in total (each picture ≤ 1 MB, total capacity ≤ 1 GB)			
	Face Picture Comparison	8-ch			
AcuSearch	By Camera	All channels *: The camera should enable AcuSearch function			
Motion Detection 2.0	By NVR	All channels, up to 4 MP (when enhanced SVC mode is enabled, up to 8 MP) video analysis for human and vehicle recognition to reduce false alarm			
	By Camera	All channels			
Perimeter Protection	By NVR	Video analysis (HD network camera, H.264/H.265) for human and vehicle recognition to reduce false alarm. Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch			
	By Camera	All channels			
Video and Audio	IP Video Input	16-ch			
	IP Speaker Input	4-ch			
	Incoming Bandwidth	160 Mbps			
	Outgoing Bandwidth	160 Mbps			
	HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz			
	VGA Output	1-ch, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz			


	Video Output Mode	HDMI/VGA independent output			
	Audio Output	1-ch, RCA (Linear, 1 KΩ)			
	Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)			
Decoding	Decoding Format	H.265, H.265+, H.264, H264+			
	Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF			
	Synchronous Playback	16-ch			
	Decoding Capability	AI on: 16-ch@1080p (30 fps) AI off: 20-ch@1080p (30 fps)			
	Stream Type	Video, Video and Audio			
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2			
Network	Remote Connection	128			
	API	ONVIF (profile S/G); SDK; ISAPI			
	Compatible Browser	IE 11, Chrome 91, Firefox 88, Safari 12, Edge 91, or above version			
	Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS			
	Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces			
Auxiliary Interface	SATA	4 SATA interfaces			
	Capacity	Up to 16 TB capacity for each HDD			
	Serial Interface	2 RS-485 (half-duplex), 1 RS-232			
	eSATA	NA	1 eSATA interface	NA	1 eSATA interface
	Alarm In/Out	16/4	16/9	16/4	16/9
	USB Interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0			
	Ctrl 12V	NA	Support	NA	Support
	DC 12V	Support			

General	GUI Language	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish, Norwegian, Finnish, Korean, Traditional Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Hebrew, Ukrainian, Indonesian
	Fan	Supports automatic speed control
	Power Supply	100 to 240 VAC, 50 to 60Hz
	Consumption	≤ 50 W (without HDD)
	Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working Humidity	10 to 90 %
	Dimension (W × D × H)	440 × 391 × 72 mm (17.32 × 15.39 × 2.82 inch)
	Weight	≤ 5 kg (without HDD, 11 lb.)
Certification	CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 55035: 2017
	Obtained Certification	CE,CB,REACH,WEEE,UKCA,RCM,IC

▪ Function


▪ Physical Interface

DS-7716NXI-K4(E)



Number	Description	Number	Description
1	LAN network interface	7	VGA interface
2	Audio out	8	USB interface
3	Audio in	9	12 VDC power input
4	HDMI interface	10	GND
5	Alarm in	11	power switch
6	Alarm out		

DS-7716NXI-K4(E)/IO16+9



No.	Description	No.	Description
1	LAN 1 and LAN 2 interfaces	6	Alarm in, alarm out, and RS-485
2	Audio in and audio out	7	GND
3	HDMI interface	8	Power supply
4	VGA interface and RS-232	9	Power switch
5	USB 3.0 interface		

▪ Available Model


DS-7716NXI-K4(E)(STD)


DS-7716NXI-K4(E)(STD)/IO16+9

DS-7716NXI-K4(E)(NEU)

DS-7716NXI-K4(E)(NEU)/IO16+9

▪ Dimension





See Far, Go Further



www.hikvision.com
support@hikvision.com

