

**NKS4223WBTH
2MP Bullet + 3MP turret WiFi NVS Kit**

- Secure and integrated video storage, all videos are stored in NVS without additional fee
- NVS equipped with Wi-Fi hotspot, one-click to add wireless cameras
- High-gain antenna design for stable camera connection and wider coverage
- NVS supports two Micro SD card slots, up to 512 GB for each card
- Smart IR and white light
- Accurate motion detection function
- Built-in mic and speaker for two-way audio
- Remote mobile phone management, all functions can be performed through Hik-Connect, such as camera adding, two-way audio, live view, playback, etc.

▪ Specification

Camera	
Power Supply	Bullet : 12 VDC \pm 25%, 0.6 A, max. 7.2 W, \varnothing 5.5 mm coaxial power plug, reverse polarity protection, *A switching adapter is included in the package. Turret : 5 VDC \pm 5%, 1.6 A, Type-C
Consumption	Bullet : Max. 7.2W Turret : Max. 8W
Working Temperature	Bullet : -30 °C to 50 °C (-22 °F to 122 °F) Turret : -10 °C to 40 °C (14 °F to 104 °F)
Working Humidity	Humidity 95% or less (non-condensing)
Dimension (W \times D \times H)	Bullet : 94.1 mm \times 75 mm \times 174.5 mm (3.7" \times 3.0" \times 6.9") Turret : 165 mm \times 155 mm \times 126 mm (6.5" \times 6.1" \times 5.0")
Weight	Bullet : Approx. 270 g (0.6 lb.) Turret : Approx. 280 g (0.6 lb.)
Camera	
Focal Length	2.8 mm
Aperture	Bullet : F1.6 Turret : F2.2
Focus	Fixed
FOV	Bullet : horizontal FOV 109°, vertical FOV 61°, diagonal FOV 125° Turret : horizontal FOV 106.4°, vertical FOV 58.4°, diagonal FOV 126.6°
Camera	
IR Range	Bullet : IR: up to 30 m ; White Light: up to 30 m Turret : IR: up to 10 m ; White Light: up to 10 m
Camera	
Video Compression	Bullet : H264 , H265 Turret : H.265
H.264 Type	Bullet : Baseline Profile, Main Profile, High Profile Turret : NA
H.265 Type	Main Profile
Video Bit Rate	Bullet : 32 Kbps to 4 Mbps Turret : 32 Kbps to 2 Mbps
Audio Compression	G.711(ulaw)/(AAC-LC)
Audio Bit Rate	64 Kbps (G.711ulaw)/16 to 64 Kbps (AAC-LC)
Audio Sampling Rate	8 kHz/16 kHz
Environment Noise Filtering	Yes


Camera	
Max. Resolution	Bullet : 1920 × 1080 Turret : 2304 × 1296
Main Stream	Bullet : 50 Hz: 25 fps (1920 × 1080, 1280 × 720, 768 × 432) 60 Hz: 30 fps (1920 × 1080, 1280 × 720, 768 × 432) Turret : 50 Hz: 20 fps (2304 × 1296, 1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2304 × 1296, 1920 × 1080, 1280 × 720)
Sub-stream	Bullet : 50 Hz: 25 fps (768 × 432) 60 Hz: 30 fps (768 × 432) Turret : 50 Hz: 20 fps (768 × 432) 60 Hz: 20 fps (768 × 432)
Image Setting	Saturation,brightness,contrast,sharpness,gain,white balance,adjustable by client software or web browser
Day/Night Switch	Day,Night,Auto,Schedule
Camera	
Alarm Trigger	Motion detection (support alarm triggering by specified target types (human and vehicle))
Protocols	Bullet : TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS, UPnP Turret : TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, UDP, QoS
General Function	Heartbeat,mirror,password protection,anti-banding
Camera	
Communication Interface	Bullet : 1 RJ45 10 M/100 M self-adaptive Ethernet port Turret : NA
Reset Button	Yes
Camera	
Camera Case Type	Bullet,Turret
Image Sensor	Bullet : 1/3" Progressive Scan CMOS Turret : 1/2.8" Progressive Scan CMOS
Min. Illumination	Bullet : Color:0.005 Lux @ (F1.6, AGC ON),B/W: 0 Lux @ (F1.6, AGC ON) Turret : Color: 0.01 Lux @ (F2.2, AGC ON),B/W: 0 Lux with IR
Day & Night	IR cut filter
WDR	Digital WDR
Angle Adjustment	Bullet : Pan: 0° to 360°,tilt:0° to 90°,rotate: 0° to 360° Turret : Pan: 0° to 345°,tilt: 15° to 85°


Protection Level	Bullet : IP66 Turret : NA
Wi-Fi Support	Yes
NVR	
IP Video Input	4-ch
Incoming/Outgoing Bandwidth	20 Mbps/20 Mbps
NVR	
Video Resolution	6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Synchronous Playback	2-ch
NVR	
Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface
NVR	
Frequency Band	2.4 GHz
Antenna Structure	Dual high gain antenna
Transmission Speed	573Mbps
NVR	
Micro SD	2 slots, up to 512GB for each card
NVR	
Power Supply	12 VDC, 1 A
Consumption (without HDD and PoE off)	≤ 12W
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	10 to 90 %
Dimension (W × D × H)	163 x 125 x 26 mm (6.4" × 4.9" × 1.0")
Weight (without hard disk)	≤ 500 g (1.1 lb)
Kit	
Accessories	Power cable: 2 × IPC power cables, 1 × NVS power cable Ethernet cable: RJ45, Cat5e UTP, 1 m
Certification	CB, CE-DOC, CE-RED, CE-LVD, CE-EMC, EN18031
Weight (with package)	≤ 2 kg (4.4 lb)
Camera	Bullet: DS-2CFW02(2.8mm) Turret: DS-2CFWQ3(2.8mm)
NVR	DS-7104NI-S2/WX

▪ Available Model



DS-J142I(STD)/NKS4223WBTH

▪ Dimension





Unit: mm (inch)



Unit: mm (inch)

See Far, Go Further



www.hikvision.com
support@hikvision.com

