

DS-KEB801X-C Panic alarm box




- One-touch emergency calling
- High quality imaging with 4 MP built-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC cards up to 256 GB
- Supports siren and audio expansion

▪ Specification

Software features	
Tamper-Proof	Tamper alarm
Intercom	1-ch built-in omnidirectional microphone, pickup distance: 5 m
Protocol	TCP/IP, RTSP, SNMP, HIK-SIP, Standard SIP, ONVIF
Hardware features	
Alarm input	2
Alarm output	2
Siren	1, sound can be configured separately
Lamp	1, light can be configured separately
Netowrk interface	2RJ45,10 M/100 M self-adaptive
Audio interface	1-ch built-in omnidirectional microphone, pickup distance: 5 m 1-ch 3.5 mm audio interface for external audio input
PSTN	1
Bus	RS-485 1, half-duplex
SD Card	Standard microSD card slot, supports microSD/SDHC/SDXC card, Max. 256 G
Video	
Resolution	2560*1440
Frame rate	PAL: 25fps ; NTSC:20fps
Field Angle	Horizontal:128° ; Vertical:75° ; Diagonal:147°
Day/night switch mode	IR cut filter
Audio	
Audio input	1-ch built-in omnidirectional microphone, pickup distance: 5 m 1-ch 3.5 mm audio interface for external audio input
Audio output	1-ch 30 W built-in loudspeaker 1-ch 3.5 mm audio interface for external audio output
Audio compression code rate	16Kbps,64Kbps
Electrical characteristics	
Power supply	220 VAC
Power Consumption	≤ 24 W
Wireless transmission	
Wired network	10 M/100 M self-adaptive Ethernet port
General	
Operation temperature	-40 °C to 70 °C
Operation humidity	10% to 90%
Dimension(WxHxD)	Without Bracket: 450 mm × 500 mm × 2205 mm (17.72" × 19.69" × 86.81") With Bracket: 450 mm × 500 mm × 4500 mm (17.72" × 19.69" × 177.17")
Installation method	Floor-mounted and pole clamp mounted
Device management	
Camera	4 MP HD IR camera

▪ Dimension



Unit:mm [inch]

SCALE	1:1
-------	-----

See Far, Go Further



www.hikvision.com
support@hikvision.com

