

Face recognition terminal is a kind of access control device. It can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens
- Recognition distance: 0.3 to 3 m
- Face recognition duration  $\leq$  0.2 s/User
- Face recognition accuracy rate  $\geq$  99%
- Built-in M1 card, Felica card, and DESfire card reading module (Presents card on the screen to authenticate)
- Face mask detection
- 100,000 face capacity, 10,000 fingerprint capacity (With fingerprint module), 500,000 card capacity, and 150,000 event capacity
- Supports ISAPI, ISUP 5.0, TCP/IP (IPv4 and IPv6)
- Supports single person and multiple people (Up to 5 people) recognition
- Support protection level IP68, IK07
- Supports face duplicate check, preventing multiple people from using the same face.
- Supports attendance-only function.
- Supports the following SIP servers: ASTERISK, 3CX, ELASTIX, miniSipServer, Brekeke, OpenSIPs, Kamailio.
- Supports Push SDK.
- Supports customized Wiegand parameters.

## ■ Specification


<b>System</b>	
Operating system	
<b>Display</b>	
Operation method	
Resolution	600 × 1024
Screen size	7 inch
Type	
<b>Video</b>	
Resolution	2 MP
Lens	Dual-lens
Video standard	PAL (Default)/NTSC
<b>Network</b>	
Wi-Fi	
Wired network	
<b>Interface</b>	
Alarm input	2
Alarm output	1
USB	1 (For Module)
Audio output interface	1 (3.5 mm)
PoE	Support, IEEE802.3at
Network interface	1
RS-485	1 RS-485. Supports OSDP protocol version V2.1.7, Baud 9600, 19200, 38400
Wiegand	1
Lock control	1
Exit button	1
Door contact input	1
TAMPER	1
<b>Capacity</b>	
Fingerprint capacity	
Card capacity	
Face capacity	
Event capacity	
<b>Authentication</b>	
Face recognition accuracy rate	≥ 99%
Card type	
Card reading distance	0 to 3 cm
Card reading duration	□ 1 s
Face recognition duration	□ 0.2 s per person
Face recognition distance	0.3 to 3 m
<b>General</b>	
Indicator	
Power supply	12 VDC to 24 VDC/2 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	0 to 90% (no condensing)
Dimensions	110.5 mm × 209.2 mm × 24 mm (4.35" × 8.24" × 0.94")
Weight	Gross Weight□1.06 kg (2.34 lb) Net Weight□0.57 kg (1.26 lb)
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Brazilian Portuguese, Japanese, Korean, Chinese Traditional, French, Turkish, Kazakh and Uzbek.
Power Output	DC12 V,0.5 A
<b>Function</b>	
Two-way audio	Support
First person in	
Time synchronization	

Face anti-spoofing	Support
Live view	Support
Audio prompt	

**Available Model**

DS-K1T673TDWX-PROE1

**Dimension**



**Accessory**

**Optional**

DS-KAB673-S1	DS-KAB6-ZU2	DS-KAB673-P	DS-KAB673-EDB	DS-KAB673-FBQR

<b>DS-KAB6-W1</b>	<b>DS-KAB673-BQR</b>	<b>DS-KAB673-B</b>	<b>DS-KAB673-A</b>	<b>DS-KAB6-ZU3</b>
				
<b>DS-KAB6-ZU1</b>				
				



© F  
ex

