LiteVMS-RM/G7/B1Userver

Intel® Core™ Processors (Kabylake-S), Cyber Hardened 1U Rackmount Appliance

PRODUCT OVERVIEW

LiteVMS-RM/G7/B1Userver is a surveillance appliance with compact design, integrated a scalable managed switch with PoE + support, powered by Intel® 7th Gen Core™ I7 CPU and provides up to 4x3.5" swappable HDD tray for sufficient storage. Featuring PoE management software and TPM 2.0 functionality, LiteVMS-RM/G7/B1Userver allows users to build a secured NVR (Network Video Recorder) application at the edge fast and easily.

All appliances are built in-house in secure facilities. Operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.





KEY FEATURES

DDR4-2400 16GB non-ECC memory, max. 32GB



Intel® 7th Gen Core™ i7-7700 processors



Onboard 24 PoE LAN ports



Four swappable HDD tray



Internal power supply 12V20A /53V5.28A for PoE



RAID Options: 0, 1, 5, 10



Cyber Hardened Video Appliance



2-Year System Warranty, 5-Year Keep Your Hard Drive Warranty

LiteVMS-RM/G7/B1Userver

BCD, Intel® Core™ Processors (Kabylake-S), Cyber Hardened 1U Rackmount Appliance

SPECIFICATIONS

Main Board

LiteVMS-RM/G7/B1Userver Intel® 7th Gen Core™ i7-7700 processors On board TPM 2.0

Main Memory

(2) x 8GB DDR4-2400 non-ECC memory, max. 32GB

LAN Features

24 x 10/100M Ethernet ports support PoE+ (max. 30W/port) Support 10/100/1000M ingress between CPU and switch 260W Power Budget @30W POE+ per port

I/O Interface-Front

Power status/HDD status/LAN status LEDs 1 x USB 3.0 port 4 x 3.5" swappable HDD tray

I/O Interface-Rear

1x HDMI port 1 x DP port 1 x Power button switch 2 x USB 3.0 ports 1 x RJ45 Management port 1 x RJ45 (10/100/1000M) 1 x SFP (1000M) 24 x 10/100M 802.3at PoE port

os

Windows 10 IoT, can be upgraded to Windows Server 2019 or Server 2022

Storage

1 x SATA M.2 2242/2280 Key M slot, 256GB 4 x $3.5^{\prime\prime}$ HDD swappable bay support Software RAID 0,1,5,10

Power Input

Internal power supply 12V20A /53V5.28A for PoE

Dimensions

Chassis dimension: 486mm x 483mm x 44mm Carton dimension: 775mm x 576mm x 221mm

Weight

Without packing: 14 kg With packing: 17.5 kg

Environment

Operating temperature: 0°C ~ 40°C Storage temperature: -40°C ~ 80°C Relative Humidity: 10% ~ 90% non-condensing

Certifications

CE FCC Class A UL

Warranty

2-Year Hardware, 5-Year Keep Your Hard Drive Warranty

ORDERING INFORMATION

Barebone

LiteVMS-RM/G7/B1Userver (P/N: TBC)

Supports Intel® 7th Gen Core™ i7-7700 processors, 2 DDR4 memory slots, 24 10/100 PoE LAN ports, M.2 socket, USB ports, HDMI/DP port, 4 swappable 3.5" HDD bays