

**DS-D4515CB135-2FQ/A**

DS-D4515CB135-2FQ/A 135" LED AIO LED Module Spare Part



300 × 168.755 Indoor LED Module

- LED modular spare part of DS-D4515CB135-2FQ

## ▪ Specification

<b>Product Model</b>	
Product Model	DS-D4518CB135-2FQ/A
<b>Product Type</b>	
Product Type	Small Pixel Pitch Indoor Full-color LED Display
<b>Cabinet</b>	
Pixel Configuration	SMD Triad LED
Pixel Pitch	1.5625 mm
Pixel Pitch Category	P1.5
Pixel Density	409600 dots/m <sup>2</sup>
Maintenance Method	Front maintenance for all components
<b>Module</b>	
Dimensions	300 × 168.75 mm
Module Resolution	192 × 108
<b>Display</b>	
White Balance Brightness	600 cd/m <sup>2</sup>
Color Temperature	3000-10000 K adjustable
Viewing Angle	160°(H)/160°(V)
Contrast Ratio	3000:1
Color Uniformity	≤ ± 0.003Cx , Cy
Brightness Uniformity	≥ 97%
<b>Processing Performance</b>	
Driving Method	Constant current driving
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	16 bit
<b>Power</b>	
Input Voltage	100~240 VAC ± 10%
<b>Working Environment</b>	
Working Temperature	-10 °C to 40 °C (14 °F to 104 °F )
Working Humidity	20% to 80% RH (without condensation)
Storage Temperature	-10 °C to 50 °C (14 °F to 122 °F )
Storage Humidity	10% to 90% RH (without condensation)
<b>General</b>	
G.W.	0.379 kg
Net Weight	0.345 kg

## ▪ Available Model

DS-D4515CB135-2FQ/A(All-in-one)

## ▪ Accessory

### ▪ Included

<b>DS-1NP6UEC0</b>	<b>DS-D40W-2F</b>	<b>DS-D40W-2F/PC</b>	<b>DS-D40W-2F/HU B</b>
			

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

