

ISD-SMG908L-S(C)

Intelligent Classification Walk-Through Metal Detector

The ISD-SMG908L-S(C) walk through metal detector that is capable of intelligent Classification, high sensitivity and strong anti-interference can carry out metal detection for person and effectively identify illegal items. It can be used in enterprises, factory workshops, prisons, governments, office buildings, schools, hospitals, cultural and museum scenic spots, large-scale security activities and other scenarios.



- **Intelligent Classification:** In intelligent classification mode, specified metal items can be detected and alarm, such as electronic products(phone, earphone, etc), prohibited Items (knife, etc), but the daily necessities(key, belt, etc) can be alarm.
- **Metal detection:** In metal detection mode, one coin-size metal (approx. $\phi 25\text{mm}$) can be effectively detected and detect non-ferromagnetic metals such as copper, aluminum, zinc with weight over 10 grams..
- **Positioning Light:** Two doorposts are equipped with LED light bar, can intuitively display the area where prohibited items are located.
- **Networking:** Allow user use a web browser to edit remotely the configuration parameter of the device.
- **Modular Design:** The components are modular designed and are easy to maintenance and transport.
- **Display:** Support a 10.1-inch LCD color touch screen, can display important information such as alarm passage numbers, alarm numbers, time / date etc.
- **People Counting:** Bi-lateral IR sensor can accurately detect the number of people passing through the detector.
- **Self-test:** supports self-test of the system and displays the test result.
- **Environmental interference detection:** It supports detecting whether there is environmental interference and can automatically switch to the optimal frequency band.
- **Health & Safety:** Comply with international standards, it is harmless to people with heart maker, pregnant woman etc.


▪ Specification

▪ Size	
Tunnel Size	2002 mm(H) × 746 mm(W) × 625 mm(D)
Dimension	2240 mm(H) × 912 mm(W) × 706 mm(D)
Package Size	Case: 875 mm(L) × 785 mm(W) × 350 mm (H) Planks : 2325 mm(L) × 785 mm(W) × 350 mm (H)
▪ Performance	
Detection Accuracy	Metal detection mode: One coin size(approx. ϕ 25mm) metal; Intelligent Classification mode: electronic products(phone, earphone, etc), prohibited Items (knife, etc) alarm, but daily necessities(key, belt, etc) do not alarm.
Detection Zones	8
Sensitivity Levels	1 ~ 100
Frequency Setting	System frequency 1~10 optional, support custom frequency
Predefined scenes	5 sets of performance parameters can be customized, and support fast switching between scenes 1-5 and applying corresponding performance parameters
▪ Safety & Control	
Log in Method	Password
Control Method	Touch screen, web browser
▪ Display	
Parameter	One 10.1-inch LCD color touch screen
▪ System Functions	
Standard	Time / Date, passage counting, power on self-diagnostics, sensitivity adjustment, frequency adjustment, environment calibration, multi detection mode, built-in multi detection mode, match automatically frequency, programmable random alarm capability, programmable alarm output, system information management and alarm parameters management, etc.
▪ Interface	
Network Interface	1 RJ45 Ethernet port.
Power interface	1 AC power interface
Alarm output	2 relay output
▪ Device Parameters	
Power Supply	AC 100 ~ 240V, 50 / 60Hz
Power Consumption	Max. 40W
Operation Temperature / Humidity	-10 °C to 55 °C / 0 % to 95 % (non-condensing)
Weight	Net: approx. 73 kg; Gross: approx. 84 kg Case (include package): approx. 20 Kg; Planks (include package): approx. 64 Kg
▪ Other	
Camera	Optional

▪ Available Model

ISD-SMG908L-S(C)(O-STD)

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq