

DS-QAZ1630G1-BE **Network Frameless Ceiling Speaker PoE 30W**




- 1 × 1.0-inch tweeter and 1 × 6.5-inch woofer
- Rated Power: 30 W
- Sensitivity(1 m, 1 W): 92 dB
- Max. SPL: 104 dB
- Frequency Response: 80 Hz to 20 kHz
- Support Hi PoE
- Support schedule/live/emergency broadcast, alarm linkage, two-way audio, TTS
- White or black appearance optional

▪ Specification

Protocol	
Network Protocol	IPv4, HTTP, HTTPS, SIP, SSL/TLS, DNS, NTP, TCP, UDP, IGMP, ICMP, DHCP, ARP
Microphone	
Type	MEMS
Amount	2
Frequency Response	100 Hz to 10 kHz
Sensitivity	-38dBV/Pa
Speaker	
Impedance	8Ω
Rated Power	30W
Total Harmonic Distortion (THD)	≤1%
Sensitivity(1 m, 1 W)	92dB
Max. Acoustic Pressure	104dB
Frequency Response	80Hz~20kHz(-10dB)
Speaker Unit	1 × 1.0-inch tweeter and 1 × 6.5-inch woofer
Coverage Angle	Conical Coverage: 90°
Function	
Audio Algorithm	AEC、AGC、ANS、DRC
Audio Bit Rate	G.711ulaw (64 Kbps) /G.711alaw (64 Kbps) /MP3 (128 Kbps) Sampling bit width: 16 bits
Speech Synthesis	Language Type: English, Russian, Spanish, Japanese, Thai, Portuguese (Brazil), Korean, French
Interface	
Alarm	Alarmin
Network Interface	RJ45 10 M/100 M Adaptive Ethernet port × 1
Local Storage	Built-in 64 GB EMMC (Audio file storage is 55 GB.)
Audio In	3.5 mm audio interface × 1
LED Indicator	Solid green: normal working Flashing green: intercom in progress Solid red: start or network disconnection Flashing red: upgrading
Reset	Support
General	
Power	24 VDC ± 10%, 2.5 A, max. 60 W, PoE: 50 V to 57 V, 0 A to 1.6 A, max. 71 W
Material	Main body: PC Base: ABS
Mounting Hole Dimension	Ø270 mm (10.63")
Dimension	Ø286.74 mm × 213.6 mm (11.29" × 8.41")
Weight	Approx. 2.7 kg (5.95 lb.)
Language	41 languages: English, French, Spanish, German, Italian, Japanese, Thai, Russian, Portuguese (Brazil), Arabic, Bulgarian, Czech, Danish, Greek, Spanish (Mexico), Estonian, Persian, Finnish, Hebrew, Croatian, Hungarian, Indonesian, Kazakh, Korean, Kirgiz, Lao, Lithuanian, Latvian, Dutch, Norwegian, Polish, Portuguese, Romanian, Slovak, Slovenian, Serbian, Swedish, Turkish, Ukrainian, Uzbek, Vietnamese

Package Dimension	350 mm × 350 mm × 343 mm (13.78" × 13.78" × 13.5")
With Package Weight	Approx. 2.9 kg (6.49 lb.)
Packing List	Device × 1 Regulatory Compliance and Safety Information × 1 2-pin phoenix connector × 1 4-pin phoenix connector × 1
Bluetooth	Bluetooth 5.0, 10 m
Operating Temperature	-10 °C to 45 °C
Operating Humidity	< 90% (No condensation)
Mounting Depth	240 mm (9.45")

▪ Dimension



Unit: mm [inch]

SCALE	1:1
-------	-----

See Far, Go Further



www.hikvision.com
support@hikvision.com

