

DS-PDMCS-EG2-WE(B) Wireless Slim Magnet Detector



DS-PDMC-EG2-WE is a wireless opening detector that notifies of first signs of room intrusion by means of a broken door or window. It can be mounted on all types of doors including metal base and the onboard inputs will allow user to extend applications by wiring to different wired sensors.

- Slim design for an unobtrusive (unnoticeable) installation
- Fully remote configurable through APP
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission



Specification

Detection Performance					
Detection Method	Opening Contact				
Detection Gap	43 mm Max				
Feature					
Digital Processing	Support				
Tamper Protection	Front,Rear				
Environment Temperature	Support				
Indicator	συμμοιτ				
Signal Strength Indicator	Support				
Interface					
AlarmInput	Normally Closed, Normally Open, Impulse Count				
Power Switch	Power up enrolling				
LED Indicator	Blue (alarm)				
Transmission					
Transmission Technology	Tri-X Wireless				
Transmission Method	Two-Way RF Wireless				
Transmission Frequency	868MHz				
Transmission Security	AES-128 Encryption				
Transmission Range(Free Space)	1.6Km				
Frequency Hopping	Support				
Enrolling Method	Power up,Remote ID,QR Code				
Electrical Characteristics					
Standard Battery Life	Up to 5 years (standby time)				
Power Supply	Battery powered				
Battery Type	CR2450 x 1				
Typical Voltage	3V				
General					
Operation Temperature	-10°C to 55°C (14°F to 131°F)				
Storage Temperature	-20°C to 60°C (-4°F to 140°F)				
Operation Humidity	10% to 90%				
Dimension(WxHxD)	24mm × 104mm × 24.4mm				
	13 mm × 34.4 mm × 11.4 mm				
Weight	59 g				
Application Scenario	Indoor				

Available Model

DS-PDMCS-EG2-WE(B)/BLACK

DS-PDMCS-EG2-WE(B)/BLACK/DZ

DS-PDMCS-EG2-WE(B)

DS-PDMCS-EG2-WE(B)/DZ/POLAND

Accessory

Optional

DS-PDB-MC-Adapt	DS-PDB-MCS-DGra	DS-PDB-MCS-Brow	DS-PWA96-Kit1-WE	DS-PWA96-Kit2-WE
er	у	n		











DS-PWA96-Kit-WE



See Far, Go Further



www.hikvision.com support@hikvision.com















