

DS-2XE6086G0-LIS(316L) Explosion-proof Fixed Bullet Camera



- Explosion-proof design: the camera has passed international ATEX & IECEx certifications, and can be used in gas and dust hazardous scenarios
- IP66/IP68 water resistant, preventing water ingress for outdoor use
- Vandal resistant (IK10)
- H.265+/H.265/H.264 encoding: efficient compression technology saves storage space and reduces bandwidth requirements
- /AM : Built-in armored cable

▪ Specification

Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	3840x2160
Min. Illumination	Color: 0.003 Lux @ (F1.2, AGC ON), B/W: 0.0001 Lux @ (F1.2, AGC ON)
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV 108°, vertical FOV 58°, diagonal FOV 132° 4 mm, horizontal FOV 88°, vertical FOV 46°, diagonal FOV 104°
Aperture	F1.6
Illuminator	
Supplement Light Type	IR, White Light
Supplement Light Range	IR: up to 30 m White Light: up to 30 m
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 12.5 fps (3840×2160, 3072×1728, 2560×1440, 1920×1080, 1280×720) 60 Hz: 12.5 fps (3840×2160, 3072×1728, 2560×1440, 1920×1080, 1280×720)
Sub-Stream	50 Hz: 12.5 fps (1280×720, 640×480, 640×360) 60 Hz: 12.5 fps (1280×720, 640×480, 640×360)
Third Stream	50 Hz: 10 fps (1920×1080, 1280×720, 704×576, 640×480) 60 Hz: 10 fps (1920×1080, 1280×720, 704×480, 640×480)
Video Compression	Main stream: H.265+/H.265 Sub-stream: H.265/H.264/MJPEG Third-stream: H.265/H.264
Video Bit Rate	32 Kbps to 16Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Main Profile
Scalable Video Coding (SVC)	H.264 and H.265 encoding
Region of Interest (ROI)	5 fixed region for main stream
Audio	
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate	64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/48 kHz
Environment Noise Filtering	Yes
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SFTP, ARP, SNMP, WebSocket, WebSockets, RTCP
Simultaneous Live View	Up to 20 channels
API	ONVIF (Profile S, Profile G, Profile T), ISAPI, SDK, ISUP
User/Host	Up to 32 users 3 user levels: administrator, operator, and user

Security	Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-MD5), WSSE and digest authentication for ONVIF, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, security audit log, control timeout settings
Client	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	Plug-in required live view: IE 10, IE 11 Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Edge 89+, Safari 11+ Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+
Image	
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser
Day/Night Switch	Day, Night, Auto, Schedule, Alarm Trigger
Wide Dynamic Range (WDR)	120 dB
Image Enhancement	BLC, HLC, 3D DNR, Distortion Correction
Privacy Mask	8 programmable polygon privacy masks
Picture Overlay	LOGO picture can be overlaid on video with 128 × 128 24 bit bmp format.
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB, *You are recommended to purchase memory card together with the product if needed. After ordering, the memory card will be installed to product during manufacturing.
Audio	1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium, 1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium
Alarm	1 input, 1 output (max. 5 VDC, 0.1 A)
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error), alarm input and output
Smart Event	Unattended baggage detection, object removal detection, scene change detection, audio exception detection, defocus detection
Linkage	Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, audible warning, white light flashing
Deep Learning Function	
Perimeter Protection	Line crossing, intrusion, region entrance, region exiting Support alarm triggering by specified target types (human and vehicle)
Face Capture	Detects up to 10 faces simultaneously, Supports swing left and right from -60° to 60°, tilt up and down from -30° to 30°, Uploads face with background and closed-up face pictures
General	
Power	PoE: IEEE 802.3af, Class 3, max. 7.5 W, 12 VDC ± 20%, 0.5 A, max. 6 W, 3-core terminal block
Material	SUS316L with anti-corrosion coating

Dimension	DS-2XE6086G0-LIS(316L):157.8 mm × 137.4 mm × 136.5 mm (6.21" × 5.41" × 5.37") DS-2XE6086G0-LIS(316L)(2.8mm)5m(海外标配)/样机,DS-2XE6086G0-LIS(316L)(4mm)5m(海外标配)(样机),DS-2XE6086G0-LIS(316L)(2.8mm)1.3m(海外标配)@,DS-2XE6086G0-LIS(316L)(4mm)1.3m(海外标配)/样机:157.8 mm × 137.4 mm × 136.5 mm (6.21" × 5.41" × 5.37") DS-2XE6086G0-LIS/AM(316L)(2.8mm)5m(海外标配),DS-2XE6086G0-LIS/AM(316L)(4mm)5m(海外标配)@,DS-2XE6086G0-LIS/AM(316L)(2.8mm)1.3m海外标配,DS-2XE6086G0-LIS/AM(316L)(4mm)1.3m(海外标配):225.7 mm × 137.3 mm × 136.5 mm (8.88" × 5.41" × 5.37")
Package Dimension	DS-2XE6086G0-LIS(316L):396 mm × 236 mm × 222 mm (15.59" × 9.29" × 9.22") DS-2XE6086G0-LIS/AM(316L)(2.8mm)1.3m海外标配,DS-2XE6086G0-LIS/AM(316L)(4mm)1.3m(海外标配),DS-2XE6086G0-LIS(316L)(2.8mm)1.3m(海外标配)@,DS-2XE6086G0-LIS(316L)(4mm)1.3m(海外标配)/样机:396 mm × 236 mm × 222 mm (15.59" × 9.29" × 9.22") DS-2XE6086G0-LIS/AM(316L)(2.8mm)5m(海外标配),DS-2XE6086G0-LIS/AM(316L)(4mm)5m(海外标配)@,DS-2XE6086G0-LIS(316L)(2.8mm)5m(海外标配)/样机,DS-2XE6086G0-LIS(316L)(4mm)5m(海外标配)(样机):562 mm × 236 mm × 222 mm (22.12" × 9.29" × 9.22")
Weight	Approx. 2700 g (5.95 lb.)
With Package Weight	Approx. 3400 g (7.50 lb.)
Startup and Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language	33 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian
General Function	Heartbeat, mirror, flash log, password reset via e-mail, pixel counter, anti-banding
Cable Length	1.3 m or 5 m (4.26 ft. or 16.40 ft.)
Approval	
EMC	CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7, KC: KN32: 2015, KN35: 2015

Safety	CB: IEC 62368-1:2014+A11, CE-LVD: EN 62368-1:2014/A11: 2017, BIS: IS 13252 (Part 1): 2010/IEC 60950-1:2005, LOA: IEC/EN 60950-1
Protection	IP66: IEC 60529-2013, IP68: IEC 60529-2013, IK10: IEC 62262:2002
Explosion-Proof Protection	ATEX: Ex II 2 G D Ex db IIC T6 Gb/Ex tb IIIC T80 °C Db IP68 IECEx: Ex db IIC T6 Gb/Ex tb IIIC T80 °C Db IP68 For explosive gas atmospheres, the maximum surface temperature is 85 °C; For flammable dust atmospheres, the maximum surface temperature is 80 °C; IIC: for explosive gas atmospheres other than mines susceptible to firedamp; For explosive gas mixture atmospheres: Zone 1, Zone 2, Zone 21, Zone 22.
Anti-Corrosion Protection	NEMA 4X (NEMA 250-2018)

▪ Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.


This model has top-level protection.


Level	Description
Top-level protection	Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more.
Moderate protection	Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain.
No specific protection	Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed.





▪ Available Model

DS-2XE6086G0-LIS/AM(316L)(2.8mm)5mO-STD
DS-2XE6086G0-LIS/AM(316L)(4mm)5m
DS-2XE6086G0-LIS/AM(316L)(2.8)1.3mO-STD
DS-2XE6086G0-LIS/AM(316L)(4mm)1.3mO-STD
DS-2XE6086G0-LIS(316L)(2.8mm)5m
DS-2XE6086G0-LIS(316L)(4mm)5m
DS-2XE6086G0-LIS(316L)(2.8mm)1.3m
DS-2XE6086G0-LIS(316L)(4mm)1.3m

▪ Dimension











Unit: mm [inch]

SCALE	1:1
-------	-----



Unit: mm [inch]

SCALE 1:1

▪ Accessory

▪ Optional

DS-2XE2601-5-Y(SS))	DS-2XE2601-1-Y(SS))	DS-1269ZJ-P-Y	DS-2XE2705-M04(3 16L)	DS-4401ZJ-GY38SL YHinge
				

See Far, Go Further



www.hikvision.com
support@hikvision.com

