


# DS-K1T342 Series MinMoe Release Notes

## (2026-2-4)


<p><b>Device Model:</b>  DS-K1T342E(W)X  DS-K1T342EFWX  DS-K1T342M(W)X  DS-K1T342MF(W)X,  DS-K1T342D(W)X</p> <p>DS-K1T342E(W)X-E1  DS-K1T342EFWX-E1,  DS-K1T342M(W)X-E1  DS-K1T342MF(W)X-E1  DS-K1T342D(W)X-E1</p> <p><b>Naming Rule:</b>  <b>D</b> for Desfire card, Felica card and M1 card,  <b>M</b> for M1 card, <b>E</b> for EM card,  <b>F</b> for fingerprint, <b>W</b> for Wi-Fi,  <b>E1</b> for POE</p>	Firmware Version	<p><b>ARM:</b>  <a href="#">ACS_342_F1pro_EN_NEU_V4.48.0_build260128</a>  <a href="#">ACS_342_F1pro_EN_STD_V4.48.0_build260128</a></p> <p><b>Note:</b> POE version and non-PoE version use the same firmware</p>
	Software	<p><b>HikCentral AC:</b>  <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-4-0/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-4-0/</a></p>

### New features



#### 1. Support push SDK




#### 2. Support to upgrade “Secure Door Control Unit” in web page




### 3. Support fuzzy search by personnel ID or name in web page




### 4. Add video intercom features (batch import and activate sub door stations & indoor stations, configure network parameters, voice mailbox, sync community-building-unit info and master station info to sub door stations & indoor stations)




## 5. Support authentication linkage settings based on user types



## 6. Support to verify audio sampling rate when importing audio files



## 7. Support to fill zero and transfer to wiegand34 format (10 digitals) in output direction, as long as the length of original card number doesn't exceed 8 digitals



## 8. Support to directly export events from web page and view it

The screenshot displays the HIKVISION web interface for Access Control. On the left, there is an 'Event Search' sidebar with filters for Event Types, Major Type, Sub Type, Employee ID, Name, Card No., Start Time, and End Time. A red box highlights the 'Export All Events' button. The main area shows a table of event logs with columns: No., Employee ID, Name, Card No., Card Reader ID, Door, Event Types, Time, Remote Host IP, Unit, Alcohol Concentration, Status, and Opera. Below the table, there is a pagination control showing 'Total: 39' and '20' items per page.

No.	Employee ID	Name	Card No.	Card Reader ID	Door	Event Types	Time	Remote Host IP	Unit	Alcohol Concentration	Status	Opera
1	--	--	--	--	--	Remote Logi...	02-04-2026 15:00:06	10.19.141.124	--	--	--	--
2	--	--	--	--	--	Remote Logi...	02-04-2026 14:59:44	10.19.141.124	--	--	--	--
3	10086	III	--	1	1	Authenticate...	02-04-2026 14:39:02	--	--	--	--	--
4	--	--	--	--	--	Remote Man...	02-04-2026 14:35:21	10.9.96.43	--	--	--	--
5	10086	III	--	1	1	Authenticate...	02-04-2026 04:42:12	--	--	--	--	--
6	10086	III	--	1	1	Authenticate...	02-04-2026 04:42:08	--	--	--	--	--
7	10086	III	--	1	1	Authenticate...	02-04-2026 04:42:05	--	--	--	--	--
8	10086	III	--	1	1	Authenticate...	02-04-2026 04:42:01	--	--	--	--	--
9	10086	III	--	1	1	Authenticate...	02-04-2026 04:41:53	--	--	--	--	--
10	10086	III	--	1	1	Authenticate...	02-04-2026 04:41:48	--	--	--	--	--
11	10086	III	--	1	1	Authenticate...	02-04-2026 04:41:45	--	--	--	--	--
12	10086	III	--	1	1	Authenticate...	02-04-2026 04:40:56	--	--	--	--	--
13	10086	III	--	1	1	Authenticate...	02-04-2026 04:40:53	--	--	--	--	--
14	--	--	--	--	--	Remote Logi...	02-04-2026 04:36:47	10.19.141.124	--	--	--	--
15	--	--	--	--	--	Remote Logi...	02-04-2026 04:36:29	10.19.141.124	--	--	--	--
16	--	--	--	--	--	Remote: Login	02-04-2026 04:23:19	10.9.96.43	--	--	--	--
17	--	--	--	--	--	Standard SIP...	02-04-2026 04:15:28	10.9.96.245	--	--	--	--
18	--	--	--	--	--	Network Rec...	02-04-2026 04:15:26	--	--	--	--	--
19	--	--	--	--	--	IP Address C...	02-04-2026 04:12:56	10.9.96.35	--	--	--	--
20	--	--	--	--	--	Remote: Logn	02-04-2026 04:11:57	10.9.96.43	--	--	--	--

Below the table, there is an 'Event List' section with a grid view showing columns: Employee ID, Name, Card No., Event Major Type, Event Sub Type, Time, Remote Host IP, Door ID, Reader ID, and Serial No.


Employee ID	Name	Card No.	Event Major Type	Event Sub Type	Time	Remote Host IP	Door ID	Reader ID	Serial No
			Operation	Remote: Login	2026/01/16	10.18.37.116			34
			Operation	Remote: Logout	2026/01/16	10.18.37.116			35
		1883288981	Event	No Card No. Found	2026/01/16		1	1	36
		1883288981	Event	No Card No. Found	2026/01/16		1	1	37
		0443668882	Event	No Card No. Found	2026/01/16		1	1	38
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	39
			Event	Door Open (Door	2026/01/16		1		40
			Event	Door Closed (Door	2026/01/16		1		41
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	42
			Event	Door Open (Door	2026/01/16		1		43
			Event	Door Closed (Door	2026/01/16		1		44
		1883288981	Event	No Card No. Found	2026/01/16		1	1	45
		1883288981	Event	No Card No. Found	2026/01/16		1	1	46
			Operation	Remote: Login	2026/01/16	10.18.37.116			47
			Operation	Remote: Logout	2026/01/16	10.18.37.116			48
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	49
			Event	Door Open (Door	2026/01/16		1		50
			Event	Door Closed (Door	2026/01/16		1		51
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	52
			Event	Door Open (Door	2026/01/16		1		53
			Event	Door Closed (Door	2026/01/16		1		54
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	55
			Event	Door Open (Door	2026/01/16		1		56
			Event	Door Closed (Door	2026/01/16		1		57
10086	111 111	0443668882	Event	Access Granted by	2026/01/16		1	1	58
			Event	Door Open (Door	2026/01/16		1		59
			Event	Door Closed (Door	2026/01/16		1		60
		1883288981	Event	No Card No. Found	2026/01/16		1	1	61
			Operation	Remote: Login	2026/01/16	10.9.96.42			62
			Event	Access Granted by	2026/01/16		1	1	63
			Event	Door Open (Door	2026/01/16		1		64
			Event	Door Closed (Door	2026/01/16		1		65

## 9. Add Kazakh language and Uzbek language

The screenshot shows the 'System Configuration' page in the HIKVISION web interface. The 'Basic Information' section is active, displaying various system parameters. The 'Language' dropdown menu is open, showing 'English' as the selected option. Other visible options include Portuguese(Brazil), 日本語, 한국어, 繁體中文, Türkçe, Français, O'zbekcha, and Қазақша. The 'Web Version' is V3.2.94\_8034011 BUILD 250128, and the 'Plugin Version' is V3.0.7.41.

Parameter	Value
Device Name	Access Controller
Language	English
Product Name	Português(Brazil)
Serial No.	日本語
Firmware Version	繁體中文
Encoding Version	Türkçe
Hardware Version	Français
Web Version	O'zbekcha
Plugin Version	Қазақша
Available Video Channels	V3.2.94_8034011 BUILD 250128
IO Input Number	V3.0.7.41
IO Output Number	1
IO Output Number	0
IO Output Number	0

## 10. Add new picture formats: .jpg, .png and .bmp




## Optimizations

### 1. Support to manually enable ONVIF in local page



### 2. Optimize finger printer authentication algorithm

### 3. Optimize remote verification features (*remote verification credential types, user-define authentication result text and voice prompt, default authentication channel is ISAPI*)



4. Person information will be removed when switch from door station mode to outer door station mode

The screenshot displays the HIKVISION web management interface. At the top, there is a navigation bar with the HIKVISION logo on the left and menu items: Access Control, Video Intercom (highlighted in red), Person Management, Device, and System and Maintenance. On the right of the navigation bar, there are icons for help, refresh, and a user profile labeled 'admin'. Below the navigation bar, a sub-menu is visible with options: No. Settings, Video Intercom Network, Call Settings, Press Button to Call, Call Priority, and Number Settings. The main content area shows the 'Call Parameters' configuration for a device. It includes three dropdown menus: 'Device Type' (set to 'Door Station'), '\*Floor No.' (set to 'Door Station'), and '\*Door Station No.' (set to '0'). A 'More' link with a downward arrow is located below these dropdowns. At the bottom of the configuration area, there is a red 'Save' button.

# DS-K1T342 Series MinMoe V4.39.180\_build250912

## Release Notes (2025-10-31)

<p><b>Device Model:</b>  DS-K1T342E(W)X  DS-K1T342EFWX  DS-K1T342M(W)X  DS-K1T342MF(W)X,  DS-K1T342D(W)X</p> <p>DS-K1T342E(W)X-E1  DS-K1T342EFWX-E1,  DS-K1T342M(W)X-E1  DS-K1T342MF(W)X-E1  DS-K1T342D(W)X-E1</p> <p><b>Naming Rule:</b>  <b>D</b> for Desfire card, Felica card and M1 card,  <b>M</b> for M1 card, <b>E</b> for EM card,  <b>F</b> for fingerprint, <b>W</b> for Wi-Fi,  <b>E1</b> for POE</p>	Firmware Version	<p><b>ARM:</b>  ACS_342_F1pro_EN_NEU_V4.39.180_build250912  ACS_342_F1pro_EN_STD_V4.39.180_build250912</p> <p><b>Note:</b> POE version and non-PoE version use the same firmware</p>
	Software	<p><b>HikCentral AC:</b>  <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-4-0/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-4-0/</a></p>

### Optimizations

1. Optimize ISUP related function and stability
2. Optimize fingerprint and face picture/modeling data synchronization logic. New firmware supports to assign face pictures that are large than 200KB, and fingerprints that are larger than 512KB
3. Optimize device activation process
4. Optimize SIP/VOIP/Platform calling process
5. Optimize QR code algorithm
6. Optimize TTS working logic
7. Fix DST (daylight saving time) issue. After rebooting, the device DST remains correct

## DS-K1T342 Series MinMoe V4.38.0\_build250307

### Release Notes (2024-07-09)

<b>Device Model:</b> DS-K1T342E(W)X, DS-K1T342EFWX, DS-K1T342M(W)X,DS-K1T342MF(W)X, DS-K1T342D(W)X  DS-K1T342E(W)X-E1, DS-K1T342EFWX-E1, DS-K1T342M(W)X-E1,DS-K1T342MF(W)X-E1, DS-K1T342D(W)X-E1  <b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi <b>E1</b> for POE	Firmware Version	<b>ARM:</b> <a href="#">ACS_342_F1pro_EN_NEU_V4.38.0_build250307</a> <a href="#">ACS_342_F1pro_EN_STD_V4.38.0_build250307</a>  <b>Note:</b> POE version and non-PoE version use same firmware
	Software	<b>HikCentral AC:</b> <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-3-1/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-3-1/</a>

#### Optimizations

Optimize the firmware to improve production efficiency

## DS-K1T342 Series MinMoe V4.38.0\_build250109


### Release Notes (2024-07-09)

<b>Device Model:</b> DS-K1T342E(W)X, DS-K1T342EFWX, DS-K1T342M(W)X,DS-K1T342MF(W)X, DS-K1T342D(W)X  DS-K1T342E(W)X-E1, DS-K1T342EFWX-E1, DS-K1T342M(W)X-E1,DS-K1T342MF(W)X-E1, DS-K1T342D(W)X-E1  <b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi <b>E1</b> for POE	Firmware Version	<b>ARM:</b> <a href="#">ACS_342_F1pro_EN_NEU_V4.38.0_build250109</a> <a href="#">ACS_342_F1pro_EN_STD_V4.38.0_build250109</a>  <b>Note:</b> POE version and non-PoE version use same firmware
	Software	<b>HikCentral AC:</b> <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-3-1/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-3-1/</a>


#### New Features

## ● Video intercom

1. Supports preview before answering for VoIP
2. In the remote door opening event of a SIP call, the room number can be uploaded
3. Support the door station being called
4. Optimized intercom audio encoding capabilities, improving audio sampling rate




5. Modify the maximum call duration for intercom from 180 to 300




6. Support configuration of up to 3 VoIP servers

### SIP Server List:

ASTERISK, 3CX, ELASTIX, miniSipServer, Brekeke, OpenSIPs, Kamailio




## 7. Support configuration of SIP call mode




8. Support returning to the home page during a call on the screen
9. Support returning to the call interface after a call timeout
10. Support automatic dialing from the dialing interface
11. Support one-click call to the VoIP center

**Remark:** Added VoIP center as call center. When you push calling center button, the VoIP center will be called.



12. Support linkage calls for authentication failure

**Remark:** if authentication failed attempts reached the set number, it will automatically call button settings's calling target.




13. The main screen supports one-click call to the VoIP center

14. Support Hik-Connect Team Cloud Intercom

15. Support intercom mode configuration


**Remark:** The main screen can be configured with call modes, and the function buttons can be customized.




## ● Access control

### 1. Support multi-door interlock between devices


**Remark:** Users can configure the doors of different devices as interlock groups, and if one of the doors in the interlock group is open, the other doors cannot be opened.






2. Support multi-door interlock delay for door opening in the device

**Remark:** form 0 to 255 seconds.




3. Support cross-device anti-passback as a slave device configuration


**Remark:** It is paired with a customized version firmware of DS-K1T805FW(V1.8.1 build ) who is used as anti-passback server.




**Area Antiback:** The entry and exit of people in the area must be matched, otherwise it will not be passable.



**Route Antiback:** Personnel must be certified in turn according to the set route, and the passage is only one way.




#### 4. Support locking door when door close




- **Others**

1. Multi-language added: Chinese traditional, French, Turkish
2. Support ONVIF stream fetching




### 3. Support sub-stream 320x240

**Remark:** sub-stream is an independent stream that is separated from the main stream during the video encoding process and used for a specific purpose or device.



### 4. Support remote verification based on different person type

**Remark:** You can choose different person type to join the remote verification. The 342 support platform anti-pass back with HikCentral platform by using this configuration.




5. Support report device online status by SNMP

6. Support operator user type in personnel information: Administrator, Operator, Basic Person


**Remark:** Administrator can edit all configurations of the device. Operator just can edit person. Basic Person can't edit any configuration of the device.

7. Support alarm prompt for door opening timeout
8. Support for connecting to one OSDP card reader

9. Support uploading door magnetic events to Hik-Connect
10. Support enabling and disabling custom prompt sounds



## 11. Support configuration of device time display format



## 12. Support automatic screenshot when calling the Hik-Connect app

The screenshot displays the HIKVISION web interface for Access Control. The top navigation bar includes 'Access Control' and 'Video Intercom'. The left sidebar contains 'Event Search', 'Access Control Application', and 'Access Control Parameters'. The main content area is titled 'Privacy Settings' and includes the following sections:

- Authentication Result Display Duration:** A dropdown menu set to '5'.
- Picture Uploading and Storage:**
  - Save Picture When Auth.:** Enabled (toggle switch).
  - Upload Picture When Auth.:** Enabled (toggle switch).
  - Captured Picture Mode:** Radio buttons for 'Default' (selected) and 'Face Picture Matting'.
  - Max. Picture Size:** Dropdown menu set to 'Unlimited'.
  - Picture Resolution:** Dropdown menu set to 'Auto'.
  - Save Registered Picture:** Enabled (toggle switch).
  - Save Pictures After Linked Capture:** Enabled (toggle switch).
  - Upload Picture After Linked Capture:** Enabled (toggle switch).
  - Upload Captured Picture During Call:** Enabled (toggle switch), highlighted with a red box.
- Clear All Pictures in Device:**
  - Clear Registered Face Pictures:** Button labeled 'Clear'.
  - Clear Captured Pictures:** Button labeled 'Clear'.
- PIN Mode:** Radio buttons for 'Platform-Applied Personal PIN' (selected) and 'Device-Set Personal PIN'.

A red 'Save' button is located at the bottom of the settings area.

13. Modify the detection period of the alarm input

14. Support personnel attendance only without opening the door after verification

**Remark:** If enable this button in person configuration. The lock will not be open after authentication ,only Attendance records take effect.

HIKVISION®
Access Control Video Intercom
Person

⊖ 1

---

**Basic Information**

Employee ID 1

Name

Gender  Male  Female  Unknown

Person Type  Normal User  Visitor  Blocklist User  Custom Type

Person Role  Basic Person  Administrator  Operator

Long-Term Effective User

Validity Period  -

Attendance Check Only  After enabling, this person won't be given access control permission.

## DS-K1T342 Series MinMoe V3.16.1\_build240701 Release Notes (2024-07-09)

<p><b>Device Model:</b> DS-K1T342E(W)X, DS-K1T342EFWX, DS-K1T342M(W)X,DS-K1T342MF(W)X, DS-K1T342D(W)X</p> <p>DS-K1T342E(W)X-E1, DS-K1T342EFWX-E1, DS-K1T342M(W)X-E1,DS-K1T342MF(W)X-E1, DS-K1T342D(W)X-E1</p> <p><b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi <b>E1</b> for POE</p>	Firmware Version	<p><b>ARM:</b> ACS_342_F1pro_EN_NEU_V3.16.1_build240701 ACS_342_F1pro_EN_STD_V3.16.1_build240701</p> <p><b>Note:</b> POE version and non-PoE version use same firmware</p>
	Software	<p><b>HikCentral AC:</b> <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-2-0/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-2-0/</a></p>

### Reason of Upgrade

Enhance products quality and meet customers' requirements.

### Modified features

1. Optimize the fingerprint collection and synchronization function from Hik-Connect cloud.

## DS-K1T342 Series MinMoe V3.16.1\_build230802 Release Notes (2023-08-22)

<p><b>Device Model:</b> DS-K1T342E(W)X, DS-K1T342EFWX, DS-K1T342M(W)X,DS-K1T342MF(W)X, DS-K1T342D(W)X</p> <p>DS-K1T342E(W)X-<b>E1</b>, DS-K1T342EFWX-<b>E1</b>, DS-K1T342M(W)X-<b>E1</b>,DS-K1T342MF(W)X-<b>E1</b>, DS-K1T342D(W)X-<b>E1</b></p> <p><b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi <b>E1</b> for POE</p>	<p>Firmware Version</p>	<p><b>ARM:</b> ACS_342_F1pro_EN_NEU_V3.16.1_build230802 ACS_342_F1pro_EN_STD_V3.16.1_build230802</p> <p><b>Note:</b> POE version and non-PoE version use same firmware</p>
	<p>Software</p>	<p><b>HikCentral AC:</b> <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-0-1/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-0-1/</a></p>

**Reason of Upgrade**

DS-K1T342 **PoE Series** are released for the first time.




**New Features**

2. Max.1500 faces capacity, Max.3000 fingerprints capacity (model with F only), and Max.3000 cards
3. 4.3-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in EM/M1/Desfire card reading module
4. Two-way audio with iVMS/HikCentral software, indoor station, main station and Hik-Connect App;

- Supports TCP/IP, Wi-Fi (model with W only)
- 5. Configuration via the web client and enroll face picture with mobile phone camera.
- 6. Face Recognition Distance: 0.3 m to 1.5 m; Duration < 0.2 s/User; Accuracy rate ≥ 99%
- 7. IP65 protection level
- 8. Power supply by standard PoE(af) and at the same time powers supply for door lock (max 12 VDC/1 A)

**K1T342-E1 series  
powered by PoE**



**Note:** Only when device is powered by PoE, it will have power output for the lock, if the device is powered with 12V DC adapter, please power the lock with power adapter.

- 9. Supports platform-applied personal PIN and device-set personal PIN.

## DS-K1T342 Series MinMoe Terminal

### V 3.16.1\_build230802 Release Notes (2023-08-08)


<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX <b>Naming Rule:</b> D for Desfire card, Felica card and M1 card M for M1 card, F for fingerprint, W for Wi-Fi	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_NEU_V3.16.1_build230802 ACS_342_F1pro_EN_STD_V3.16.1_build230802
	Software	<b>HikCentral AC:</b> <a href="https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-0-1/">https://www.hikvision.com/en/support/download/software/hikcentral-access-control-v2-0-1/</a>

**Reason of Upgrade**

Add new function, fix bugs, enhance products quality and meet customers' requirements.

## New Features


### 1. User friendly web design



### 2. PIN Code supports switching between platform applied personal PIN mode and device set personal PIN mode

Notice :


Open web client, go to Configuration-Security-Password mode to switch PIN Code mode. In platform applied mode, cannot edit PIN Code on web client, it needs to be set on platform. In device set mode, can edit PIN Code on web client or local UI and PIN code set by platform is invalid.




### 3. Support sync person information to platform automatically

Notice:


- a. Platform requirement: HCP V2.4.1 or HCAC V2.1.1
- b. Only ISAPI or ISUP protocol supported
- c. Need to set up on platform first. If you enable this function , changes of the person information will be synced from the device to the platform automatically




4. Supports modifying device password locally





5. Supports enable M1 encryption locally




- Support modify I frame interval (NTSC 30 or PAL 25) both on web and local menu.



- Supports 2 anti-spoofing detection level: **General** and **Advanced**. It supports to customize anti-spoofing threshold in advanced settings



8. Supports QR code 2.0
9. Support capture network package on web client



## DS-K1T342 Series MinMoe Terminal Release Notes (2022-03-09)

<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX <b>Naming Rule:</b> D for Desfire card, Felica card and M1 card M for M1 card, F for fingerprint, W for Wi-Fi	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_STD_V3.3.5_build220210 ACS_342_F1pro_EN_NEU_V3.3.5_build220210
	SDK	Latest baseline version
	iVMS-4200 Version	Latest baseline version

### Reason of Upgrade

Add new function, fix bugs, enhance products quality and meet customers' requirements.

### Modified features

1. Fix the problem that the device cannot wake up occasionally after running for a long time;

## DS-K1T342 Series MinMoe Terminal Release Notes (2022-01-04)

<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_STD_V3.3.5_build211229 ACS_342_F1pro_EN_NEU_V3.3.5_build211229
--	------------------	---

DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX	SDK	Latest baseline version
<b>Naming Rule:</b> D for Desfire card, Felica card and M1 card M for M1 card, F for fingerprint, W for Wi-Fi	iVMS-4200 Version	Latest baseline version

**Reason of Upgrade**

Add new function, fix bugs, enhance products quality and meet customers' requirements.

**Modified features**

2. Update the driver to be compatible with the new fingerprint module;
3. Fixed some issues about ISAPI protocol;

## DS-K1T342 Series MinMoe Terminal Release Notes (2021-12-10)

<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX  <b>Naming Rule:</b> D for Desfire card, Felica card and M1 card M for M1 card, F for fingerprint, W for Wi-Fi	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_STD_V3.3.5_build211122 ACS_342_F1pro_EN_NEU_V3.3.5_build211122
	SDK	Latest baseline version
	iVMS-4200 Version	Latest baseline version

**Reason of Upgrade**

Add new function, fix bugs, enhance products quality and meet customers' requirements.

**Modified features**

4. Optimize the display of Hik-Connect QR code in the UI background;
5. Repair some protocol issues;

## DS-K1T342 Series MinMoe Terminal Release Notes (2021-11-12)

<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX <b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_STD_V3.3.5_build211110 ACS_342_F1pro_EN_NEU_V3.3.5_build211110
	SDK	Latest baseline version
	iVMS-4200 Version	Latest baseline version

### Reason of Upgrade

Add new function, fix bugs, enhance products quality and meet customers' requirements.

### Modified features

1. Update the driver to be compatible with new fingerprint materials;

## DS-K1T342 Series MinMoe Terminal Release Notes (2021-10-25)

<b>Device Model:</b> DS-K1T342EX, DS-K1T342EWX DS-K1T342EFWX, DS-K1T342MX, DS-K1T342MWX DS-K1T342MFX, DS-K1T342MFWX DS-K1T342DX, DS-K1T342DWX <b>Naming Rule:</b> <b>D</b> for Desfire card, Felica card and M1 card <b>M</b> for M1 card, <b>F</b> for fingerprint, <b>W</b> for Wi-Fi	Firmware Version	<b>ARM:</b> ACS_342_F1pro_EN_STD_V3.3.5_build211014 ACS_342_F1pro_EN_NEU_V3.3.5_build211014
	SDK	Latest baseline version
	iVMS-4200 Version	Latest baseline version

## Reason of Upgrade

New model DS-K1T342 series MinMoe terminal first time released.




## New Features


1. 4.3 inch LCD touch screen, 2 MP wide-angle dual-lens camera; IP65 protection level;
2. Connect external card reader or access controller via RS485 protocol; support Wiegand26/34 output
3. Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
4. **Face, card, fingerprint, event capacity**

Model	Face	Card	Fingerprint	Event	Wi-Fi
DS-K1T342EX	1,500	3,000(EM)	Not support	150,000	Not support
DS-K1T342EWX			Not support		Support
DS-K1T342EFWX			3,000		Support
DS-K1T342MX	1,500	3,000(M1)	Not support	150,000	Not support
DS-K1T342MWX			Not support		Support
DS-K1T342MFX			3,000		Not support
DS-K1T342MFWX	1,500	3,000	3,000	150,000	Support
DS-K1T342DX			Not support		Not support
DS-K1T342DWX			(Desfire, Felica, M1)		Not support

5. **ISAPI** protocol makes it easier for integration with third-party software;
6. Remote video intercom and unlock door from **Hik-Connect App** on your mobile/Pad
7. Support **Hik-ProConnect** platform to realize Cloud access control and time attendance management
8. Support **ISUP 5.0** protocol to manage devices located in different locations;
9. When open device for the first time, **wizard for activation and basic configuration**. Including select language, application mode, select and configure network, Hik-Connect, privacy settings, add administrator face and card
10. Self-defined shortcut key (Call Room, Call Center, Call Specified Room, Call App and Password) on main interface;



11. Configure ISUP and Hik-Connect parameter in device local menu



12. Login and configure device in web client via **PC** **browser**



©2021 Hikvision Digital Technology Co., Ltd. All Rights Reserved.

**13. Support audio file import and replace the default voice prompt**


**Note:** imported file format

wav format, mono, sampling rate 8K or 16K, size no more than 512K


The screenshot shows the 'Configuration' page for the 'Prompt' section. The 'Custom Prompt Importing' option is selected and highlighted with a red box. Below it, there is a 'Custom Prompt' section with a 'Custom Type' dropdown menu set to 'Calling Center...' and an 'Import' button. A table lists various custom prompts and their importing status.

Custom Type	Importing Status	Operation
Calling Center...	Not Imported	
The Call Is Refused.	Not Imported	
Nobody Answered	Not Imported	
Please Try Again Later	Not Imported	
Thanks	Not Imported	
Authenticating Failed	Not Imported	
Authenticated	Not Imported	
The Door Is Open	Not Imported	
Please Wear the Mask	Not Imported	

**14. The displayed authentication result text can be customized**, edited through the web, including the scope of the results of stranger, authentication success and authentication failure.



15. Self-defined voice prompt (TTS function, English only) and screen display info (user ID, name and face picture) for authentication;




## 16. Network


Support TCP/IP and Wi-Fi (model with W only), adapt to LAN(network) or WAN(ISUP 5.0) network environment.

## 17. Function


- Support face mask recognition.
- Video intercom with indoor station, master station and platform;
- Multiple verification modes: Face, card, fingerprint(-F only), PIN code;
- Support check in/check out/break out/break in/overtime in/overtime out attendance status, and self-define status name;



e. Support custom standby background image (max 8 pictures)



f. Support privacy protection, customer can define the privacy related parameter, such as Event Storage Settings, Picture Uploading and Storage, Clear All Pictures in Device



## **Customer Impact and Recommended Action**

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

### Note:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.  
No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,  
China  
Tel: +86-571-8807-5998  
FAX: +86-571-8993-5635  
Email: [overseabusiness@hikvision.com](mailto:overseabusiness@hikvision.com)