

## DS-PA201PG-32WB Control Panel



- Simple and elegant appearance design
- Wi-Fi and GPRS network for cloud communication
- Friendly app interface makes installation and use easier
- Up to 1200 m radio signal transmission range in open space

## • Specification

Capacity	
ARC	1
Installer	3
User	12
Areas	8
Wireless zones	32
Wireless keypads	4
Wireless sounders	4
Wireless keyfobs	16
Logs	1000
Admin	1
Communication	
Transmission technology	433.1-433.7 MHz
Transmission range (free space)	up to 1,200 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Encryption	AES-128
Ethernet	1 8P8C socket
Ethernet speed	≤10Mbps
Wi-Fi	802.11 b/g/n
Cellular	GPRS
SIM slots	1
Software features	
Upgrade OTA	Yes
Protocol	SIA-DCS *SIA-DCS ADM-CID *ADM-CID OTAP Other proprietary protocols
Notifications	
APP notifications	Yes
SMS notifications	Yes
Calls notifications	No
ARC notifications	Yes
Event types	Alarms Faults System Events Operations
Indication	
Indication method	LED
Hardware features	
Tamper-Proof	Yes



Power Supply	
Mains power	110-240 V~, 50/60 Hz
Power consumption	max current: 0.2 A quiescent current: 90 mA
Electrical characteristics	
Built-in backup battery	Yes
Battery life	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
Battery charging temperature	0 °C to +40 °C
General	
Dimension (W×H×D)	165 x 165 x 37.5 mm
Weight	407 g
Operation temperature	-10 °C to +55 °C
Operation humidity	10% to 90%
Shell material	Plastic

#### ▪ Available Model

DS-PA201PG-32WB

#### ▪ Accessory

#### ▪ Optional

DS-PZ201ADB-CO M	DS-PC201N
	

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

