

DS-QAE0206G1-V
Analog Ceiling Speaker 6W



- Adopting a composite paper fiber sound basin, the sound quality is clear and bright
- With the design of powerful steel spring clamp, the installation is fast and safe
- Support ceiling mounting installation with a simple appearance

▪ Specification



Speaker	
Impedance	8 Ω
Speaker Unit	5.25" × 1
Coverage Angle	Conical Coverage: 95°
Audio	
Rated Power	6 W
Sensitivity	91 dB \pm 3 dB
Max. Acoustic Pressure	98 dB
Frequency Response	90 Hz to 20 kHz
Interface	
Audio In	Rated voltage , 100 V
General	
Material	Shell: ABS; Mesh enclosure: iron mesh
Operating Condition	-20 °C~50 °C (-4 °F to 122 °F), humidity: 95% or less
Dimension	\varnothing 170 × 64 mm (\varnothing 6.69" × 2.52")
Package Dimension	173.5 × 173.5 × 67 mm (6.83" × 6.83" × 2.64")
Weight	Approx. 468.5 g (1.03 lb.)
With Package Weight	Approx. 534 g (1.18 lb.)
Packing List	Device × 1 Regulatory Compliance and Safety Information × 1
Mounting Hole Dimension	\varnothing 148 mm (\varnothing 5.83")

*The device should be used together with amplifier.

▪ Available Model

DS-QAE0206G1-V

▪ Dimension



Unit: mm(inch)

See Far, Go Further



www.hikvision.com
support@hikvision.com

