

DS-K3BK420LX **Kindergarten Turnstiles**



- 4 pairs of IR light detectors: Permissions validation and anti-tailgating.
- Valid passing duration settings: System will cancel the passing permission if a person does not pass through the lane within the valid passing duration.
- Without built-in access control board and card readers (optional).
- High quality SPCC steel with colorful coating, stable and sturdy structure, beautiful appearance and vivid color.
- Fire linkage: When the fire signal is triggered, the barrier will be open automatically for emergency evacuation.

▪ Specification

System	
Motor	brushless motor
MCBF	≥ 3 million times
Operating system	NA
IR light detectors	4 pairs
Brake	Not support
Interface	
Exit button	Main: 1 Sub: 1
Fire alarm input	1
Hardware	
Access controller	Not supplied
Supercapacitor	Supplied
General	
Throughput	20 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method.
Lane width	600 mm to 750 mm (23.62" to 29.53")
Barrier material	10 mm acrylic glass
Pedestal material	SPCC 1.2mm
Indicator	NA
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	0% to 95% (No condensing)
Dimensions	Without package: 1200 mm × 220 mm × 900 mm (47.24" × 8.66" × 35.43") With package: 1255 mm × 275 mm × 960 mm (49.41" × 10.83" × 37.80")
Weight	Net: Left: 53 kg (116.84 lb) Middle: 60 kg (132.28 lb) Right: 55 kg (121.25 lb) Gross: Left: 63 kg (138.89 lb) Middle: 70 kg (154.32 lb) Right: 65 kg (143.30 lb)
Approval	CE/CB/RoHS/REACH/WEEE
Power supply method	Power supply: 100 to 240 VAC~, 50/60 Hz, 0.7A
Power supply for face recognition module	Support
Configuration	
Module selection	NO
Application environment	indoor and outdoor (waterproof)

▪ Available Model

DS-K3BK420LX

- **Accessory**
- **Optional**

DS-K1T673TDX
Ultra Series Face
Access Terminal



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq