

DS-52EX01HI-4K HDMI Extender



Product Introduction

The HDMI Extender, when paired with NVRs/DVRs, allows you to transmit 4K resolution video through Ethernet cables for the distance of up to 120 meters. It also supports remote control of video recorders via USB controller.

Key Feature


- Up to 4K resolution and stable 120 m long-distance transmission
- Compatible with major video recorders in the market
- Plug-and-play, synchronous transmission of video and audio
- No latency in video image, extraordinary user experience



Specification

Video and Audio	
	Receiver: 1-ch
HDMI Output	Resolution: 4K (3840 × 2160)/60 Hz, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz,
	1920 × 1080p/60 Hz, 1080 × 720/60 Hz
HDMI Input	Transmitter: 1-ch
	Resolution: 4K (3840 × 2160)/60 Hz, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz,
	1920 × 1080p/60 Hz, 1080 × 720/60 Hz
Auxiliary Interface	
Serial Interface	Transmitter: 1, console interface
	Receiver: 1, console interface
USB Interface	Transmitter: 1
	Receiver: 1
General	
Power Supply	12 VDC, 1 A
Consumption	Transmitter: ≤ 5 W
	Receiver: ≤5 W
Working Temperature	-10 °C to 45 °C (14 °F to 113 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	Transmitter: $96 \text{ mm} \times 60 \text{ mm} \times 26 \text{ mm} (3.76" \times 2.36" \times 1.02")$
	Receiver: 96 mm \times 60 mm \times 26 mm (3.76" \times 2.36" \times 1.02")
Weight	≤ 1 kg
Others	
Power Indicator	Transmitter: 1 power indicator
	Receiver: 1 power indicator
Video Transmission	
Transmission Interface	1, RJ45
Transmission Distance	Resolution for 120 m transmission distance (with Cat6 Ethernet cable):
	4K (3840 × 2160)/30 Hz, 1920 × 1080/60 Hz, 1080 × 720/60 Hz
	Resolution for 100 m transmission distance (with Cat5e Ethernet cable):
	4K (3840 × 2160)/30 Hz, 1920 × 1080/60 Hz, 1080 × 720/60 Hz
	Resolution for 60 m transmission distance (with Cat6/Cat5e Ethernet cable):
	4K (3840 × 2160)/60 Hz, 2K (2560 × 1440)/60 Hz


Typical Application




Note: Please use Cat6 (recommended) or Cat5e Ethernet cables.



Physical Interface






Available Model

DS-52EX01HI-4K



Dimension



See Far, Go Further



www.hikvision.com support@hikvision.com















