

DS-D4280GO-2AAA **P8.0 Outdoor LED Display Unit**



- Adopt energy-saving scheme, RGB LED IC power supply accurate distribution, energy consumption reduced by 40%+
- Well-designed heat dissipation scheme to cope with hot weather without air conditioner
- Use aviation plug to transmit power and signal between the cabinet, with excellent sun protection and corrosion resistance
- The aluminum cabinet features high flatness of splicing and weighs only 28 kg.
- Meet CE/CB and other international certification standards, stable and reliable quality


▪ Specification

Cabinet	
Modules Component	3 × 2
Resolution	120 × 120
Module	
Pixel Configuration	SMD Triad LED
Pixel Pitch Category	P8.0
Pixel Pitch	8 mm
Lamp Bead Dimensions	2727
Dimensions (W × H × D)	960 mm (W) × 960 (H) mm × 100 (D) mm (37.795" × 37.795" × 3.973")
Area	0.9216 m ²
Weight	27.8 Kg (61.29 lb.)
Pixel Density	15625 dots/m ²
Maintenance Method	Front/Rear maintenance
Waterproof Level	IP66
Component Material	Aluminum Profile
Key Material	
Lamp Encapsulation	2727 (gold wire)
Control System	Hikvision
Display	
White Balance Brightness	≥ 9000 cd/m ²
Color Temperature	9300K adjustable
Viewing Angle	Horizontal 160°, vertical 130°
Contrast Ratio	≥ 8000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Frame Frequency	50/60 Hz
Refresh Rate	Up to 3840 Hz
Grey Level	14 to 16 bit adjustable
Power	
Power Supply	110 to 220 VAC ± 15%
Max. Consumption	≤ 485 W/m ² (9000 nits)
Average Consumption	≤ 162 W/m ² (9000 nits)
Working Environment	
Working Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Working Humidity	10% RH to 95% RH (No condensation)
Storage Humidity	10% RH to 95% RH (No condensation)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
General	
Gross Weight	32.35 kg /1 in 1 (71.32 lb.)
Package Dimension (W × H × D)	1140 (W) mm × 1068 (H) mm × 244 (D) mm (44.882" × 42.047" × 9.606")
Lifespan	Lamp 100,000 hours

▪ Available Model

DS-D4280GO-2AAA

▪ Dimension



Unit: mm [inch]

SCALE	1:3
-------	-----

▪ **Accessory**

▪ **Optional**

DS-D42CD-1AAB/R Receiving card for DS-D42XXCD-1AAB	DS-D42-PC Power cable for DS-D42XXCD-1AAB	DS-D42-NC Network cable for DS-D42XXCD-1AAB	DS-D42-PC/NC Power cable and Network cable for 2AAA, 1AAB and 2APA series	MCP400WCD-4.2/3.2 power supply for DS-D42CO-2APA series
				
DS-D42CO-1APA/H HUB board for DS-D42CO-2APA series	DS-D4280GO-2AAA/M Module for DS-D4280GO-2APA/M			
				

See Far, Go Further



www.hikvision.com
support@hikvision.com

